

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 2 Page(s) 697)

-----  
Set ¼ sec. post; from which  
A fir, 5" dia., bears N.40°E., 17 lks.  
A fir, 60" dia., bears South, 14 lks.

-----  
Wilford N. Haines - For: Harold Woolley - Dec. 1957 - M8-30

-----  
Scribed - 16" fir S.71°17'W., 78.1 ft.  
Set - 1"x1"x36" ⊥ rod with brass cap.

-----  
Tony Hostetter - For: Seneca Jones Timber Co. - 6/2008 - M156-13

-----  
Found - Bent "T" post set by Haines (M8-30)  
32" Fir BT w/tag bears S.70°30'W., 78.9 ft.  
New BTs- 12" Fir, scribed "S26 ¼ BT" bears N.42°26'E., 12.6 ft to spike.  
12" Maple scribed "S35 ¼ BT" bears S.45°22'E., 7.7 ft to spike.  
11" Fir, scribed "S35 ¼ BT" bears S.58°29'W., 21.6 ft to spike.

-----  
Fd as per record 12/2017 - D. Edwards C.S. File 65/97-7