

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 711)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on N face; from which
 Fir, 20" dia., bears N.3°E., 31 lks., mkd: ¼ S BT.
 Fir, 36" dia., bears S.10°W., 56 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging - Dec. 1961 - M21-74 & M21-75 & C.S. File 51/222-6

Found - 20" Fir N.3°E., 31 lks., wood scribe.
 36" Fir S.10°W., 56 lks, bark scribe.
Set - 1"x1"x36" T iron & scribed:
 9" I.Cedar S.42°W., 31.4 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - 11/28/1961 - C.S. File 49/143-13

Found - Haines "T" iron at cor. (no cap)
 Fir tree (now 36" dia.) N.3°E., 20.5 ft. (slope measurement) has been opened previously. Good scribing "¼" visible on old face.
 Fir tree (now 60" dia.) S.10°W., 36.9 ft. (slope measurement) did not open.
 9" Cedar S.40°W., 11.5 ft., recently scribed (in wood). MKD: "¼ S26 BT"