TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 714)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 48" dia., bears N.21°E., 43 lks., mkd: ¼ S BT.
Fir, 10" dia., bears S.31°W., 67 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - Dec. 1961 - C.S. File 49/143-22

Found - 48" fir, now 72", uprooted & down, N.21°E., 28.4 ft.
Fd. very faint bark scribing "¼S" barely visible.
No trace of SW BT fd.
Set brass cap at cor. mkd: County Surveyors T21S R6W ¼ S11/S14
Office, 1961
New BTs- 20" fir S.55°E., 13.4 ft., mkd: ¼ S14 CS BT
15" forked hemlock N.37°E. 46.0 ft. mkd: ¼ S11 CS BT

Douglas Co. Surveyors Office - Gary Langlitz - Clell Goodwin - M. Lenora Ladig - 12/20/1975 - C.S. File 57/39-29

Found - A 1"x30" IP w/brass cap from County Surveyor 1961, properly mkd., from which
The stump hole from a 72" blown down fir bears N.21°E., 28.4 ft.
A 24" fir alive & well healed bears S.55°E. 13.4 ft.
A 15" hemlock with visible scribe marks bears N.37°E., 46.0 ft. now blown down.
New BT - A 13" hemlock scribed "¼ S11 CS BT" in a double blaze, bears N.29°E., 16.3 ft.
Compass decl. 20° East.

Harvey Christensen - For: Seneca Jones Timber Co. - 1/1999 - M131-17

Found - 1961 DCSO 2.5" B C, 0.8 ft. above ground
24" D.Fir, S.55°E., 13.4 ft. stump
43" D.Fir, S.02°E., 81.7 ft. stump-put R.R. spike @ center
17" W. Hem, N.29°E., 16.3 ft., scribing visible
13" W. Hem, S.75°W., 53.4 ft., blazed & scribed "¼ S14 BT"
15" W. Hem, N.84°W., 39.6 ft., blazed & scribed "¼ S11 BT"
Set - 6 ft. Steel post 1 ft. North