

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 577700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, T20-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 678-79)

-----  
Set post for corner to secs. 1, 2, 35 and 36, on hillside facing North, from which

- A Fir 24" dia., bears S.45°E., 38 lks. dist.
- A Fir 5" dia., bears N.17½°E., 25 lks. dist.
- A Laurel 4' dia., bears N.45°W., 20 lks. dist.
- A Laurel 4" dia., bears S.50°W., 6 lks. dist.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 709)

-----  
Found post standing marked T20S S36 on NE.; S1 on SE.; R6W S2 on SW.; S35 on NW. face, and but one witness tree:

- Fir 24" dia., bears S.45°E., 38 lks. dist. mkd. T21S R6W S1 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - and crew - July 31, 1958 - C.S. File 49/89-1

-----  
Found - Orig. 24" now 48" Fir snag. I open and find good scribing, "BT", S.45°E., 25.1 ft.

All other BTs gone as recorded in 1884.

Also find Haines' Marker at corner.

Set Brass cap at cor. mkd: County Surveyors Office

T20S R6W S 35 | S 36  
T21S S 2

1958

New BTs- 16" R.Fir bears N.68½°W., 12.0 ft. scribed S35 T20S R6W CS BT.

12" R.Fir bears N.54°E., 45.5 ft. scribed S36 T20S R6W CS BT.

BLM Resurvey by Norman J. McDonald, Survey Technician, under Group #469, Surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13091-92)

-----  
The sec. cor., which has been perpetuated with a DCSO survey marker, an iron post 1" dia., projecting 8" from the ground, firmly set with brass cap as mkd. in 1958

from which the remaining original bearing trees:

A sawed Fir stump 26" dia., bears N.65 3/4°E., 25 lks. dist. mkd. BT on opened face, (Rec. brg. N.17½°E.)

A Fir snag, 48" dia., bears S.45°E., 38 lks. dist. mkd. BT on open blaze.

(Cont. Next Page)

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 577700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, T20-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A rotted Fir stub bears S.24 3/4°W., 20 lks. dist. mkd. BT  
(Not of record)  
Trees mkd. by the County:  
A Fir 12" dia., bears N.54°E., 68 lks. dist. mkd. S36 T20S  
R6W CS BT.  
A Fir 16" dia., bears N.68½°W., 18 lks. dist. mkd. S35  
T20S R6W CS BT.  
and new bearing trees:  
A Fir 12" dia., bears N.51°E., 75 lks. dist. mkd. T20S R6W  
S36 BT.  
A Fir 24" dia., bears N.72½°W., 33 lks. dist. mkd. T20S  
R6W S35 BT.  
I stamp USBLM 1962 on brass cap.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group  
#1231, surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47  
Page(s) 18053)

-----  
At the sec.cor., perpetuated by Haines during an unrecorded  
survey, and further perpetuated and recorded by Byron in  
1958, monumented with a "T" shaped iron rod, 1" dia., firmly  
set, projecting 6" above ground, with washer mkd. "Wilford N  
Haines 239 Survey Point Drain OR"  
from which the remains of an original bearing tree:  
A decayed Fir stump 36" dia., bears S.45°E., 38 lks.  
dist., no marks visible.  
and the remains of bearing trees mkd. by Bryon:  
A Fir 18" dia., bears N.54°E., 68 lks. dist., with healed  
double blaze.  
A sawed Fir stump 26" dia., bears N.62°E., 26 lks. dist.,  
no marks visible.  
A Fir 17" dia., bears N.68½°W., 18 lks. dist., with  
fragmentary scribe marks visible on partially healed  
double blaze.  
and a bearing tree mkd. by McDonald:  
A Fir 17" dia., bears N.52°E., 74 lks. dist., with healed  
blaze. (Rec. N.51°E., 75 lks.)  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
directly over iron rod, with brass cap mkd: T 20 S R 6 W  
S 35 | S 36  
S 2  
T 21 S R 6 W  
1984

Fd. OK, Dec. 1992 by L. Roberts - M 116-43 and C.S. 63/149-3B

(Cont. Next Page)

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 577700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, T20-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by David Wellman - For: Weyerhaeuser Co. - July 1994  
-M 120-55

-----  
CONDITION REPORT ONLY

Found:

- 2½" BLM brass cap dated 1984.
- 36" Fir, S.46½°E., 25.0 ft., visible scribing. (Rec. S.45°E., 38 lks., 1872 GLO)
- 32" Fir, N.72¼°W., 21.0 ft., closed face, record unknown.
- 18" Fir, N.68½°W., 12.0 ft., closed face.
- 19" Fir, N.52°E., 48.4 ft., closed face. (Rec. N.51°E., 75 lks., 1962 BLM)
- 20" Fir, N.53½°E., 45.0 ft., closed face. (Rec. N.54°E., 45.5 ft. 1958 DCS0)
- 26" Fir stump, N.61½°E., 17.4 ft. (Rec. N.62°E., 26 lks., 1984 BLM); (Rec. N.65 3/4°E., 25 lks., 1962 BLM); (Rec. N.17½°E., 25 lks., 1872 GLO)

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2048, surveyed June/July 2003 - (DCS0 records Vol. 55 Page(s) 21509-10)

-----  
The cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., monumented with an iron post, 2½" dia. firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree  
A decayed fir stump, 36" dia., bears S.45°E., 25.1 ft., with scribe marks BT visible on an opened blaze.  
and the remains of the BTs mkd. by Byron, in 1958

A fir stump, 21" dia., bears N.54°E., 44.9 ft., with a healed blaze.

A decayed stump, size indeterminate, bears N.62°E., 17.2 ft., no marks visible.

A fir, 23" dia., bears N. 68½° W., 11.9 ft., with a healed blaze.

and the remains of the bearing trees mkd. by McDonald

A fir stump, 20" dia., bears N.52°E., 48.8 ft., with a healed blaze.

A fir, 36" dia., bears N.72½°W., 21.8ft., with a healed blaze.

and a new accessory

An aluminum rod, 72" long, 3/4" diam., driven 72" in the ground as a reference monument, bears N.51°30'E., 22.7 ft., with aluminum cap mkd. RM T20S R6W S36 22.7FT T0 COR 2003, and an arrow pointing to the cor.

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 577700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, T20-6

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd. BC & 4 BTs, Corey Woodruff - 4/2013 - M165-16