

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T22-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 692)

Set post cor. of secs. 1, 2, 35 and 36; from which
A W.Oak 15" dia., bears N.47°W., 72 lks. dist.
A W.Oak 20" dia., bears N.5°E., 126 lks. dist.
A B.Oak 15" dia., bears S.63°W., 142 lks. dist.
A B.Oak 18" dia., bears S.25°W., 139 lks. dist.

Wilford N. Haines - For: Harold Woolley - Jan. 21, 1958 - M 8-30

Found - Orig. Oak BT to NW, stump.
Scribed -10" B.Oak S.33°E., 4.9 ft.
6" Fir N.15°E., 8.0 ft.
12" Fir N.67°W., 27.0 ft.
10" Fir S.82°W., 27.0 ft.
Set 1" x 1" x 36" Iron rod with brass cap.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Aug. 1961 - C.S. File 49/143-41

Full report typed 9/11/2017
Found - Haines "T" iron & cap
Old Oak stump N.47°W., 47.5 ft.
Old Oak stump N.5°E., 83.2 ft.
Both stumps too far gone to find any trace of old scribing.
Fd. stump hole S.25°W., 91.7 ft.
No trace fd. of orig. SE BT
Fd. following BTs with scribing not completely grown over.
14" D.Fir S.81°W., 26.9 ft.
17" D.Fir N.71°W., 27.0 ft.
14" B.Oak S.37°E., 5.2 ft.
8" D.Fir N.12°E., 7.9 ft.
Can see scribing on all these trees.
Fence cor. (fences N, S + E) bears S.84°E., 14.5 ft.

Fd. OK, Aug. 1981, R.Dean, M 88-65