

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 2 Page(s) 694-5)

Set ¼ sec. post; from which
A Fir, 8" dia., bears S.30°E., 10 lks.
A fir, 7" dia., bears S.45°W., 11 lks.

Wilford N. Haines - For: Harold Woolley - 1/21/1958 - M8-30

Set - 1"x1"x36" iron ⊥ rod with brass cap.
10" Fir (with 8" Fir curled around it) N.33°W., 6.7 ft.
28" Fir, S.33°W., 8.3 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 9/25/2001 - C.S. File 66/29-12

Found - 1958 Haines "T" iron, protrudes 8" out of ground.
28" D.Fir now roothole bears S.33°W., 8.3 ft. (1958)
10" now 17" dia., D.Fir w/fully healed single blaze bears N.33°W., 6.7 ft. (1958)
We open 2 large D.Firs approx 40" dia., trees looking for OBTs both have large growth rings not old enough.
New - 12" dia., W.Fir double blazed & scribed "¼ S36 CS BT" bears N.77°E., 22.0 ft.
9" dia., D.Fir double blazed & scribed "¼ S35 CS BT" bears N.82°W., 42.6 ft.
5" dia., D.Fir double blazed & scribed "¼ S35 CS BT" bears S.55½°W., 38.0 ft.
Compass Decl. 17½°E.