

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 2 Page(s) 695)

Set post corner to sections 25, 26, 35, & 36; from which
A fir, 8" dia., bears N.55°E., 6 lks.
A fir, 6" dia., bears S.50°E., 6 lks.
A fir, 10" dia., bears S.60°W., 5 lks.
A fir, 10" dia., bears N.50°W., 4 lks.

Wilford N. Haines - For: Harold Woolley - Dec. 1957 - M8-30

Found - Orig. BTs to NE & NW
Scribed- 9" I.Cedar S.22°50'E., 52.6 ft.
36" Fir S.57°40'W., 25.8 ft.
Set - 1"x1"x36" \perp rod with brass cap inscribed.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 9/12/2001 - C.S. File 66/29-7

Found - 1958 Haines "T" iron protrudes 7" above ground.
10" now 24" dia., D.Fir w/fully healed blaze bears
N.50°W., 3.3 ft. (Rec. N.50°W., 2.6 ft.) OBT -
Haines washer & nail in bark.
8" now 19" dia., D.Fir with a previously opened
healed blaze bears N.35°E., 4.0 ft. (rec.
N.55°E., 4.0 ft.) OBT
36" now 38" dia., D.Fir snag, bark scribed "X
S35 T21S R6 B| (the letter B with an upside
down T) with Haines washer & nail in bark,
bears S.57¾°W., 25.8 ft. (1958)
9" now 15" dia., I.Cedar with a fully healed
single blaze 3½ ft. above ground bears
S.19°E., 38.6 ft. (Rec. S.22°50'E. 52.6 ft)
(1958) We looked at rec. nothing found.
New - 14" dia., W.Fir double blazed & scribed "T21S
R6W S35 CS BT" bears S.36°W., 14.0 ft.
Compass decl. 17½°E.

Fd. Ok by D. Edwards, 8/2007 - C.S. File 65/61-10

Fd as per record 12/2017 - D. Edwards C.S. File 65/97-7