

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 2 Page(s) 695-6)

Set post corner to sections 23, 24, 25, & 26; from which
A cedar, 24" dia., bears N.50°E., 17 lks.
A cedar, 24" dia., bears S.32°E., 25 lks.
A fir, 24" dia., bears S.68°W., 42 lks.
A cedar, 24" dia., bears N.42°E., 64 lks.

Fd. & used on GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 703-4)

Wilford N. Haines - For: Woolley Logging - 1961 - M21-74

Set - 1"x1"x36" T iron from 2 orig. BTs.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy, Clete Putnam - Nov. 28, 1961 - C.S. File 49/143-12

Found - Haines "T" iron at corner, no cap.
Cedar tree, now 36", N.42°W., 42.2 ft. This tree opened previously, unmistakable but illegible traces of old scribing plainly visible on old face. Recent re-scribing found, "T21 R6W". Haines metal disc nailed to old face.
Cedar tree, now 27", S.32°E., 18.0 ft. instead of 16.5 ft. Shows axe scar. Did not open. Rescribe this tree, "T21S R6W S25 CS BT"
Rotten remains of Cedar stump N.50°E., 11.2 ft. Too far gone to find scar or scribing. No trace of SW BT.
Do Not Set Brass Cap
New BTs- 27" R.Cedar N.54°E. 26.6 ft. mkd: T21S R6W S24 CS BT
30" R.Cedar S.55½°W. 51.2 ft. mkd: T21S R6W S26 CSBT

Wilford N. Haines - Dec. 1967 - C.S. File 49/143-103

The corner common to secs. 23, 24, 25, & 26, T21S R6W. The corner is likely to be destroyed by logging operations. So I put in the ref. points shown (on map).
5/8 steel rod N.32°30'W., 122.94
101°26', [from N.32°30'W., (to the right)] 22.19 - nail in west side of 4 ft. Fir stump. (See sketch in file)
Nail in top of 4 ft. Fir stump S.32°30'E., 67.32

continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

David Edwards - For: Seneca Jones Timber Co. - 8/2007 - C.S. File 65/61-10

Section corner reset from the following:
Found - 5/8" dia., iron rod per C.S. 49/143 bears N.31°52'53"W., 122.94' (N.32°30'W.)
A 27" dia., cedar stump brs. S.55°38'W., 51.20' (S.55°30'W.) DCS
Set - 5/8"x30" steel rebar w/red plastic cap mkd: "D.A. EDWARDS - LS 2339"
8" dia., maple bears N.82°E., 18.1 ft.
12" dia., hemlock bears S.86°W., 27.8 ft.
14" dia., Fir bears N.18°W., 14.5 ft.
6 ft. steel post is set S.0°24'E., 2.0 ft.

Fd. 5/8" rebar & accessories by T.Hostetter 6/2008 - M156-13
Fd. Per 2007 rec - by D. Edwards, 1/2018 - C.S. File 65/98-3

Adam DeGroot - For: Seneca Jones Timber Co. 1/2019 - M71-55

Found - A 1"x1" T-Iron by HAINES, in 1961 per M21-74, firmly set and projecting 6" above the ground, with the original tack in top. The monument appears to be un-disturbed from the 1961-1967 HAINES & DCSO location. from which the remains of original 1871 BTs W.H. BYARS:
A 48" D.Fir stump bears S.80°43'W., 28.23 ft to a MAG-HUB in top of stump. did not open. [S.68°W., 42 LKS]
The root hole of a down 36" Cedar bears N.35°W., 42.0 ft [N.42°W., 64 LKS] (N.42°'W., 42.2 FT)
The remains of BTs mkd by DCSO in 1961 per CS 49/143-12:
A 27" rotted cedar stump bears N.47°45'E., 26.4 ft, w/illegible scribe mks on face (N.54°E., 26.6 FT)
A 28" Cedar stump bears S.59°00'W., 51.34 ft to a MAG-HUB in top of stump. No mks. (S.55°30'W., 51.2 FT)
Accessories by Haines in 1967 per CS 49/143-103:
A 5/8" iron rod bears N.31°56'50"W., 125.87 ft - not directly visible from corner (N.32'30'W., 122.94 FT)
A nail & 1.25" Haines brass washer in face of a 48" D.Fir stump bears N.62°12'E., 21.67 FT (N.68°56'E., 22.19 FT)
Accessories set by Edwards in 2007 per CS 65/61-10:
A 5/8" iron rod bears N.41°39'08"W., 3.16 FT - projecting 4" above ground - no plastic cap **cont.**

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 11" Maple bears N.71°E., 16.3 ft, w/healed blaze.
A 18" Hemlock bears N.85°45'W., 29.9 ft, w/scribe
mks. visible on part. healed blaze.
A 18" D.Fir bears N.20°W., 17.2 ft, w/healed blaze
Lat: 43°43'18.49694"N Long: 123'22'04.66058"W