

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 704)</p> <p>-----</p> <p>Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which Fir, 12" dia., bears S.47°E., 18 lks., mkd: ¼ S BT. Fir, 36" dia., bears S.87°W., 30 lks., mkd: ¼ S BT.</p>
<p>Wilford N. Haines - For: Woolley Logging - 12/1966 - M32-44</p> <p>-----</p> <p>Found - 36" D.Fir, bark scribed, now 48", rescribed below old scribe (S.87°W., 30 lks.) 12" Fir, now stub, no scribe. Set - ½" steel rod at ¼ corner. New BT - 28" Fir S.50°E., 34.1 ft.</p>
<p>Fd. ½" rod & 2 BTs, Rob Ward, 6/2001 - M138-26</p>
<p>Adam DeGroot - For: Seneca Jones Timber Co. 1/2019 - M71-55</p> <p>-----</p> <p>Found - A ½" iron rod by Haines, in 1966 per M32-44, firmly set & projecting 6" above the ground, from which the remains of an original 1884 BT by Wright: The root hole of a down 48" D.Fir bears S.87°W., 21.5 ft (S.87°W., 30 LKS] (S.87°W., 21.5 FT)</p> <p>The remains of the 1966 BT by Haines: A rotted 28" D.Fir stump bears S.50°15'E., 34.2 FT, W/rotted blaze (S.50°E., 34.1 FT) (S.50°E., 34.0 FT)</p> <p>New BTs- A 10" D.Fir bears N.52°45'E., 22.4 ft scribed "¼S24 BT" on dbl blaze A 16" D.Fir bears S.54°15'E., 19.6 ft scribed "¼S24 BT" on dbl blaze A 11" D.Fir bears S.22°30'W., 18.9 ft scribed "¼S23 BT" on dbl blaze A 12" D.Fir bears N.21°W., 30.0 ft scribed "¼S23 BT" on dbl blaze</p> <p>Lat: 43°43'44.98986"N Long: 123°22'04.66427"W</p>