

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs 13, 14, 23, & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 704-5)  
-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 13, 14, 23, & 24 mkd. T 21 S S 13 on NE, R 6 W S 24 on SE, S 23 on SW, S 14 on NW face, with 3 notches on S & 1 on E edge; from which  
    Fir, 16" dia., bears N.80°E. 60 lks. mkd: T21SR6WS13BT.  
    Hemlock, 12" dia. bears S.80°E. 64 lks. mkd: T21SR6WS24BT  
    Hemlock, 12" dia. bears S.4°W. 25 lks. mkd: T21SR6WS23BT  
    Fir, 40" dia., bears N.64°W. 11 lks. mkd: T21SR6WS14BT.

Wilford N. Haines - July 10, 1961 - C.S. File 51/27-2  
-----  
Found - 40" Fir N.62°W., 17 lks., now 56"  
        16" Fir N.80°E., 60 lks., now 34"  
        12" Hemlock S.4°W., 25 lks., gone.  
        12" Hemlock S.80°E., 64 lks., down  
Scribed stake in place & set 1"x1"x36" T iron by stake & scribed: 6" Hemlock S.42°E., 15.2 ft.  
        12" Hemlock S.53°W., 24.7 ft.

BLM remonumentation of certain orig. corner points by James E. Jelley, under group #350 surveyed April 1979 - (DCSO records Vol. 42 Page 16478)  
-----  
The cor. of secs. 13, 14, 23, & 24, perpetuated & recorded by Haines in 1961, monumented with a T shaped iron rod, 1" cross section, firmly set, projecting 8" above ground, from which the remaining orig. BT5:  
    A fir, 40" dia., bears N.80°E., 60 lks., with fragmentary scribe marks visible on partially opened blaze.  
    A fir, 56" dia., bears N.64°W., 17 lks. with healed blaze. and BTs mkd. by Haines  
    A hemlock, 8" dia., S.46°E., 24 lks., with fragmentary scribe marks visible on open blaze.  
    A hemlock, 14" dia., S.50°W., 36 lks., with fragmentary scribe marks visible on open blaze.  
At the corner point  
Set an iron post, 28" long, 2" dia., 24" in the ground, with brass cap marked:  
                                    T21S R6W  
                                    S 14 | S 13  
                                    S 23 | S 24  
                                    1979  
Reset T shaped iron rod alongside iron post.

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. Ok by Harvey Christensen, Set 6' steel post 1 ft. North - 1/1999 - M 131-17
Fd. BC & 4 BTs by Rob Ward, 6/2001 - M138-26
Adam DeGroot - For: Seneca Jones Timber Co. 1/2019 - M71-55 ----- Found - A 2½" standard USBLM iron post by JELLEY IN 1979, firmly set & projecting 4" above ground, with a 3¼" brass cap properly mkd. per the record. from which the remaining original 1884 BTS by Wright: A 44" D.Fir bears N.81°E., 40.3 ft w/re-healed blaze & Haines brass washer at face height [N.80°E., 60 LKS] A 54" D•Fir bears N.60°15'W., 12.2 ft w/healed blaze & Haines brass washer at face height [N.64°W., 17 LKS] (N.62°W., 17 LKS) AND THE 1961 BTs by Haines per CS 51/27: A 9" Rotted hemlock stump bears S.45°45'E., 16.0 ft no mks. (S.42°E., 15.2 FT) (S.46'E., 24 LKS) A 21" hemlock bears S.51°W., 23.6 FT W/HEALED BLAZE (S.53°W., 24.7 FT) (S.50°W., 36 LKS) New BT - A 14" hemlock bears S.40°'30'E., 13.5 ft scribed "T21SR6WS24 BT" on dbl blaze Lat: 43°44'11.16132"N Long:123'22'04.30075"W