

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 706)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which
Fir, 18" dia., bears N.66°W., 38 lks., mkd: ¼ S BT.
Fir, 60" dia., bears S.28°E., 42 lks., mkd: ¼ S BT.

Wilford N. Haines - 7/10/1961 - C.S. File 51/27-2

Found - 60" Fir S.28°E., 42 lks.
18" Fir, now 36" stump, N.66°W., 38 lks
Set - 1"x1"x36" T iron.
Scribed- 16" Fir S.85°E., 48.5 ft.
28" Fir N.77°W., 36.2 ft.

Douglas Co. Surveyors Office - Gary Langlitz - Clell Goodwin
- M. Lenora Ladig - 12/9/1975 - C.S. File 57/39-27

Found - 1"x1" T-iron (Haines, 1961) firmly set at the corner point, from which:
OBTs A 60" now 68" D.Fir bears S.28°E., 27.7 ft., alive, no marks visible.
A 18" fir now a 36" stump bears N.66°W., 25.1 ft. Decaying with no marks visible.
Haines BTs -
A 16" now 20" D.Fir bears S.85°E., 49.8 ft. (rec. S.85°E., 48.5 ft.) alive with bark scribe "¼ S13 BT" visible.
A 28" D.Fir now a 30" stump bears N.77°W., 36.2 ft. now marks visible.

At the corner point, we set a 1"x30" iron pipe, with brass cap attached mkd: DOUGLAS CO. SURVEYOR T21S
1975 R6W
¼ S14|S13

We place the "T-iron" along side the brass cap & mark the following New BT:

7" Hemlock N.57°W., 30.8 ft., mkd. "¼ S14 CS BT" on a double blaze.
Compass decl. 20°E

Note - This corner is located along a dirt road approx. 300 ft. from its intersection with the south fork of Smith River Access road.

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Harvey Christensen - For: Seneca Jones Timber Co. 1/1999 - M131-17

Found - 1975 DCS0 2.5" B C, 0.7
/W Haines 1"x1" "T" iron 0.4 ft above ground along West side.

BTs - 17" W. Hem N.57°W., 30.8 ft. scribing visible
42" D.Fir S.28°E., 27.7 ft. (Record) stump /w axe work-blown over
30" D.Fir S.85°E. 49.8 ft. /w axe work-Haines washer in face
19" D.Fir S.50°E., 38.0 ft. blazed & scribed "¼ S13 BT"
14" D.Fir S.25°W., 15.8 ft. blazed & scribed "¼ S14 BT"

Set - 6 ft. steel post 1 ft. North.

Fd. OK by D. Edwards 7/2007 - C.S. File 65/61-9