

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 707)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which  
Fir, 16" dia., bears S.87°W., 7 lks., mkd: ¼ S BT.  
Fir, 16" dia., bears N.58°E., 20 lks., mkd: ¼ S BT.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - Dec. 1961 - C.S. File 49/89-13

-----  
Reported as "Searched for & not fd."

Douglas Co. Surveyors Office - Larry E. Monrean - Rod B. Kimberling - 4/20/1977 - C.S. File 59/31-27

-----  
Reported as not found.  
Found a 20 ft. high snag & an uprooted stump both with BT tags. These trees have been previously opened with no sign of a blaze. These trees are both approx 20" dia., & the growth rings indicate that they are too small to be the orig. BTs.

Les Roberts - For: Seneca Timber Co. - April 20, 1993. M 116-77 & C.S. 63/153-1

-----  
Found - 16" downed Fir, N.58°E. 13.2 ft. (no marks) 1884 BT.  
(1945 GLO bearing tree tag nailed to tree)  
18" Fir stub, S.87°W., 4.6 ft. (chaining notch vis.)  
1884 BT.  
Set - 5/8" x 30" iron pin with yellow plastic cap. Iron pin set from original 1884 Southwest BT.  
New BTs- 8" Fir, N.38°W., 26.8 ft. (scribed/washer/painted red)  
12" Fir, N.31°E., 29.4 ft. (scribed/washer/painted red)  
Note - Corner lies on south slope about 150 ft. north of draw.  
Draw bears S.45°E.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1857, surveyed Sept. 1997/April 1998 - (DCSO records Vol. 53 Page(s) 20257-8)

-----  
The ¼ sec. cor. of secs. 11 & 12, perpetuated by Roberts, in 1993, monumented with an iron rod, 5/8" diam., firmly set flush with the ground, with yellow plastic cap mkd. ROBERTS PLS 1039, from which the remains of the orig. BTs  
continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole, bears N.58°E., 20 lks., with decayed down fir alongside, size indeterminate, with 1945 GLO tag and no mks. visible.

A decayed fir stump, size indeterminate, bears S.76°W., 8½ lks., with old axe marks. (Record, S.87°W., 7 lks.) and bearing trees mkd. by Roberts

A fir, 15" diam., bears N.30°E., 42½ lks., with partially healed double blaze.

A fir, 8" diam., bears N.39°W., 39 lks., with healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, directly over the iron rod, with brass cap mkd.

T 21 S R 6 W

S 11 | S 12  
          <sup>¼</sup>  
          1997

Deposit a magnet in a white plastic case at the base of the stainless steel post.