TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 709)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 24" dia., bears N.60°W., 53 lks., mkd: ¼ S BT.
Fir, 36" dia., bears S.56°E., 33 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - 1961-1962 - C.S. File 49/89-40 & C.S. 49/143-2- added 7/11/2017

Corner not found.

BLM Resurvey by Norman J. McDonald, Survey Technician, under Group #469, Surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13095)

Point for the ¼ sec. cor. of secs. 1 & 2, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 30 long, 2½" dia., 24" in the ground with brass cap marked: T21S R6W

¼
S2|S1
1961

from which
A fir, 50" dia., bears S.57°E., 112 lks., mkd: ¼ S1 BT.
A fir, 6" dia., bears N.60°W., 74 lks., mkd: ¼ S2 BT.
A 1" "T" iron, firmly set, protruding 6" from the ground, bears S.23°W., 5 lks.

Fd. Ok by L. Roberts, 12/1992 - M116-43 & C.S. File 63/149-3F