

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 2 Page(s) 695)

-----  
Set ¼ sec. post; from which (leave field)  
A W.Oak, 5" dia., bears S.45°E., 202 lks.  
A W.Oak, 5" dia., bears N.20°W., 75 lks.

-----  
Wilford N. Haines - For: Woolley Logging Co - 7/1961 - M20-76

-----  
Found - No trace of Orig. corner.  
Set - 1"x1"x36" T iron.  
5" Oak, N.75°E., 48.6 ft.  
22" Oak, S.74°W., 47.6 ft.

-----  
Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 9/11/2001 - C.S. File 66/29-6

-----  
Found - 1961 Haines "T" iron with top 10" broken off,  
remainder is plumb in ground.  
5" Oak now root hole bears N.72°E., 48.6 ft. (Rec.  
N.75°E., 48.6 ft.) 1961  
22" now 24" dia., down & rotted Oak with BT tag,  
healed blaze, root hole bears S.71°W., 47.6 ft.  
(rec. S.74°W., 47.6 ft.) 1961  
Set a 2 3/8" dia., by 32" long iron pipe at plumb position of  
"T" iron. BC/IP protrudes 4" out of ground. "T" irons set  
along north edge of BC/IP protrudes 2" out of ground. BC  
marked: DOUGLAS COUNTY SURVEYORS T21S ¼ S25/S36 R6W 2001.  
New - 4" dia., D.Fir double blazed & scribed "X BT" bears  
N.71½°W., 6.8 ft.  
10" dia., D.Fir double blazed & scribed "¼ S36 CS  
BT" bears S.58°W., 43.8 ft.  
Set a metal witness post & sign 5 ft. east of  
corner.  
No other scribe-able trees  
Compass decl 17½°E.