

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Rob Ward - For: Seneca Jones Timber Co. - June 2001 - M138-26

Set - 5/8"x36" rebar w/2½" alum. cap mkd: T21S R6W C¼
S24 2001 LS 1091

17" D.Fir bears N.43¼°W., 39.8' blazed & scribed
"C¼ S24 BT"

13" Twin Madrone bears N.85¼°E., 13.2' blazed &
scribed "C¼ S24 BT"

13" D.Fir bears S.10°E., 36.2' blazed & scribed
"C¼ S24 BT"

8" D.Fir bears S.87¼°W., 21.8' blazed & scribed
"C¼ S24 BT"

Note - BTs have red painted bands plus yellow BT tags

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - Oct.
2010 - C.S. File 65/70-10

Found - 2½" alum. cap date 2001 with the following
accessories:

20" D.Fir bears N.43¼°W., 39.8' - healed face.

13" Twin Madrone bears N.85¼°E., 13.2' - scribing
visible.

17" D.Fir bears S.10°E., 36.2' - healed face.

10" D.Fir bears S.87¼°W., 21.8' - healed face.

Adam DeGroot - For: Seneca Jones Timber Co. 1/2019 - M71-55

Found a 5/8" iron rod by Ward, in 2001 per M 138-26, firmly
set and projecting 6" above ground, with a 2½" aluminum cap
properly mkd. per the record. I did not tie the existing BTs.
This corner was directly occupied by static GPS for control.

Lat: 43°43'44.86092"N Long: 123°21'28.83663"W