

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 705)</p> <p>-----</p> <p>Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which                  Fir, 40" dia., bears N.27°E., 28 lks., mkd: ¼ S BT.                  Dogwood, 4" dia., bears S.23°E., 24 lks., mkd: ¼ S BT.</p>	
<p>Searched for, not fd 12/1961 C.S. File 49/89-13DCSO Milo Godfrey</p>	
<p>Wilford N. Haines - For: Woolley Logging - 12/1966 - M32-44</p> <p>-----</p> <p>No trace of orig. corner                  Set - ½" steel rod at corner.                  Scribed - 10" Fir S.27°W., 13.9 ft.                  7" Fir N.40°W., 44.7 ft.</p>	
<p>Rob Ward - For: Seneca Jones Timber Co. - June 2001 - M138-26</p> <p>-----</p> <p>Found - Haines ½" rebar, 48.96' West and 1.27' north of our calculated mid point.                  Set - 5/8"x36" rebar w/2½" alum. cap mkd: T21S R6W ¼ S13/S24 2001 LS 1091                  17" D.Fir bears N.4½°E., 28.1' blazed &amp; scribed "¼ S13 BT"                  16" D.Fir bears N.80¼°E., 22.2' blazed &amp; scribed "¼ S13 BT"                  14" D.Fir bears S.31½°E., 30.4' blazed &amp; scribed "¼ S24 BT"                  18" D.Fir bears S.48½°W., 26.1' blazed &amp; scribed "¼ S24 BT"                  Note - BTs have redpainted bands plus yellow BT tags</p>	
<p>Adam DeGroot - For: Seneca Jones Timber Co. 1/2019 - M71-55</p> <p>-----</p> <p>Found - 5/8" iron rod by Ward, in 2001 per M138-26, firmly set and projecting 8" above ground, with a 2 1/2" aluminum cap properly mkd. per the record. From which the 2001 BTs:                  A 20" D.Fir bears N.4°30'W., 28.3 FT w/healed blaze (N.4°30'E., 28.1 ft)                  A 19" D.Fir bears N.80°E., 22.1 ft w/healed blaze (N.80°15'E., 22.2 ft)                  A 14" D.Fir bears S.31°30'E., 30.5 ft w/healed blaze (S.31'30'E., 30.4 FT)</p>	
<p>continued next page</p>	

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 23" D.Fir bears S.48°30'W., 26.1 ft. w/healed  
blaze (S.48°30'W., 26.1 FT)  
And a reference monument by Haines in 1966 per M32-44:  
A 1/2" IRON ROD BEARS N.88°33'17"W., 48.94 FT  
(N.88°30'51"W., 48.98 FT)  
Lat: 43°44'10.75811"N Long: 123°21'28.08512"W