

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 708)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 10" dia., bears N.14°E., 23 lks., mkd: ¼ S BT.
Fir, 8" dia., bears S.45°W., 27 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - Dec. 1961 - C.S. File 49/89-13

Reported as searched for & not fd.

BLM Resurvey by Norman J. McDonald, Survey Technician, under Group #469, Surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13093)

The ¼ sec. cor. of secs. 1 & 12 determined from the remaining orig. BT:

A sawed fir stump, 28" dia., bears S.45°W., 27 lks., mkd: / S on opened blaze.

At the corner point

Set an iron post, 30" long, 2½" dia., 26" in the ground, with brass cap marked:

T21S R6W
¼ $\frac{S \ 1}{S \ 12}$
1962

from which

A maple, 17" dia., bears N.11°W., 39 lks., mkd: ¼ S1 BT.

A fir, 8" dia., bears S.39°E., 60 lks., mkd: ¼ S12 BT.

Les Roberts - For Seneca Timber Co. - April 20, 1993. M 116-77 & C.S. 63/153

Found - 1962 B.L.M. Brass Cap.

22" Fir stump S.45°W. 14.4 ft. (scribe vis.) 1884 BT

16" Maple, N.12°W., 25.5 ft. (scar vis.) 1962 BT

New BTs- 22" Fir, S.02°E., 42.1 ft. (scribed/washer/painted red)

24" Fir, N.82°W., 35.7 ft. (scribed/washer/painted red)