TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by Norman J. McDonald, Survey Technician, under Group #469, Surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13096-97)

Point for the ¼ sec. cor. of sec. 1 only, on the N. bdy. of the Tp., is at midpoint on the N. bdy. of sec. 1.
At the corner point
Set an iron post, 30" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

¼ S 1
T21S R6W
1962

from which
A Fir 26" dia., bears S.6½°E., 70 lks. dist. mkd. ¼ S1 BT.
A Fir 52" dia., bears S.46°W., 91 lks. dist. mkd. ¼ S1 BT.

BLM Resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1612, Surveyed June 1991 - (DCSO records Vol. 50 Page(s) 19221-22)

The ¼ sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1962, from which the remains of bearing trees mkd. by McDonald:
A Fir 32" dia., bears S.6½°E., 70 lks. dist. with healed blaze.
A root hole bears S.46°W., 91 lks. dist., with down Fir alongside, 45" dia., with fragmentary scribe marks visible on opened blaze.
and a new bearing tree:
A Fir 8" dia., bears S.53°W., 33 lks. dist. mkd. ¼ S1 BT.