

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T21-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 691)

-----  
Set ¼ sec. post, from which  
A W.Oak 12" dia., bears N.80°W., 106 lks. dist.  
A W.Oak 14" dia., bears S.51°E., 162 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam, crew - Oct/Nov. 1961 - C.S. File 49/143-4

-----  
Found - W.Oak now 30", S.51°E., 106.9 ft. Cut open and found good scribing.  
W.Oak now 24", N.80°W., 70.0 ft., shows 2 good scars. Did not open.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 21 S  
R6W ¼ S36|S31 R5W  
1961  
N & S fence bears West 3.4 ft.  
New BTs- 6" W.Oak S.63°E., 4.8 ft. mkd. ¼ S31 CS BT.  
7" W.Oak N.19½°W., 19.2 ft. mkd. ¼ S36 CS BT.

For: N.W. Timberland Cons. - By: Harvey Christensen - 11/10/94 - M 121-21

-----  
Condition Report Only  
Found - 1961 DCSO 2½" B.C.  
6" W.Oak, N.20°W. 19.1', healed face  
8" W.Oak, S.62°E. 4.9', snag, scribing visible  
24" W.Oak, N.79°W. 69.1', healed face, snag  
30" W.Oak, (S.51°E. 106.9'), down, rotted, out of position.