

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25; & 30, T21-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 2 Page(s) 691)

Set ¼ sec. post, from which
A Fir 40" dia., bears S.60°E., 20 lks. dist.
A Fir 6" dia., bears S.45°W., 84 lks. dist.

Wilford N. Haines, #239 - For: John Woolley - 1955 - C.S. File 42/77 and M 12-32

Let Lot Marker.
Found - 40" Fir snag, S.60°E., 20 lks.
Scribed- 5" Fir N.33°E., 8.9 ft.
18" Fir N.45°W., 27.2 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy; C. Putnam, crew - Nov. 2, 1961 - C.S. File 49/143-7

Found - Haines "T" iron & cap at fence cor - fences E, W & S
Badly burned old fir stump bears S.60°E., 13.2 ft.
No scars or scribing fd.
From monument set by Haines:
24" Fir bark scribed "¼S" (scar below) bears N.47°W., 27.8 ft.
8" Fir with scar nearly closed bears N.25°E., 9.0 ft

Fd. OK, June 1965 (no record source given, probably DCS0)

Harvey Christensen - For: Seneca Jones Timber Co. - May 2007 - M153-23

Found - 1" "T" iron with brass cap (Haines) 0.8 ft above grade.
BTs - 14" D.Fir N.30°E., 8.9 ft. healed face, (new spike), old BLM tag (9.0')
NW BT missing, replaced
3" D.Fir, N.85°W., 6,6 ft. blazed & scribed "X" "BT"
24" D.Fir S.27°E. 24.2 ft blazed & scribed "¼ S30BT"
Note - No suitable trees to south west.
Set - 6' steel post 0.5' east