

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 690)

Set post cor. of secs. 19, 24, 25 and 30, from which
A Fir 15" dia., bears N.65°E., 18 lks. dist.
A Fir 6" dia., bears S.35°E., 6 lks. dist.
A Fir 10" dia., bears N.41°W., 6 lks. dist.
A Fir 24" dia., bears S.15°W., 21 lks. dist.

GLO survey by D.W. Applegate, under Contract #351, dated May 11, 1880 - (DCSO records Vol. 2 Page(s) 816)

Found the bearing trees for cor. of secs. 24, 25, 19 and 30, still standing, but post rotted away.
Re-established cor. by building a stone mouné at the point indicated by field notes furnished, etc.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 697-98)

The Sec. Cor., which post I found much decayed. Reestablished the same by setting post, 6" dia., 4 ft. long, with mkd. stone, 12" in ground mkd. T21S S19 on NE.; R5W S30 on SE.; R6W S25 on SW.; S24 on NW. face, with 2 notches in S. and 4 in N. edge; from which old witness trees:
Fir 16" dia., bears N.65°E., 18 lks. dist. mkd. T21S R5W S19 BT.
Fir 8" dia., bears S.35°E., 6 lks. dist. mkd. T21S R5W S30 BT.
Fir 12" dia., bears N.41°W., 6 lks. dist. mkd. T21S R6W S24 BT.
Fir 26" dia., bears S.15°W., 21 lks. dist. mkd. T21S R6W S25 BT.

Wilford N. Haines, #239 - For: John Woolley - 1955 - C.S. File 42/77 and M 12-32

Set Lot Marker.
Found - 24" Fir S.15°W., 21 lks.
Scribed- 44" Incense Cedar, N.35°E., 61.1 ft.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy; C. Putnam, crew - Nov. 2, 1961 - C.S. File 49/143-6

Found - Fir snag, now 20", N.41°W., 4.0 ft., cut open and find good scribing.

Fir snag, now 32", S.15°W., 13.9 ft., no scars or scribing found.

No trace found of NE. or SE. BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T 21 S
R6W S 24 | S 19 R5W
S 25 | S 30
1961

New BTs- 6" D.Fir N.2½°E., 34.0 ft. mkd. T21S R5W S19 CS BT

18" D.Fir S.3°W., 41.3 ft. mkd. T21S R6W S25 CS BT

20" R.Cedar S.78°E., 68.6 ft. mkd. T21S R5W S30 CSBT

No suitable trees near to NW.

"T" iron and cap set by Haines, bears N.4°W., 13.6 ft.

BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19055-56)

The Sec. Cor., perpetuated by Godfrey in 1961, monumented with an iron post, 1¼" dia., firmly set, projecting 10" above ground, with brass cap mkd. in 1961, from which the remains of the original bearing trees:

A rotted Fir snag, size indeterminate, bears S.15°W., 21 lks. dist., no marks visible.

A Fir snag 20" dia., bears N.41°W., 6 lks. dist. with scribe marks S24 T21S visible on opened blaze.

and bearing trees mkd. by Godfrey:

A Fir 15" dia., bears N.3°E., 51½ lks. dist., with healed double blaze.

An Incense Cedar 29" dia., bears S.76°E., 104 lks. dist., with healed blaze.

A root hole bears S.3°W., 62½ lks. dist., with down Fir alongside, 18" dia., no marks visible on decayed open double blaze.

and new bearing trees:

A Fir 12" dia., bears S.44°W., 18½ lks. dist., mkd. T21S R6W S25 BT.

A Fir 14" dia., bears N.26½°W., 28 lks. dist., mkd. T21S R6W S24 BT.

From this point, a point established for the cor., by Haines (Cont. Next Page)

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-5

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

in 1955, bears N.3°37'00"W., 0.205 chs., dist., monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 5" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., from which a bearing tree mkd. by Haines:

An I.Cedar 52" dia., bears N.37°E., 89½ lks. dist., with healed blaze.

This point is not properly positioned and is not utilized in this survey.

Harvey Christensen - For: Seneca Jones Timber Co. - May 2007
- M153-23

Found - 2.5' dia. 1961 BC missing (windfall destroyed, no trace).

1" T-iron with brass cap, N.0°45'17"W., 13,5 ft. (Haines) 0.4 ft above grade.

Set - 5/8" x 30" rebar with 2.5" AC stamped "2007 LS 2603" 0.1 ft above grade.

BTs - 17" D.Fir N.3°E., 33.7 ft. healed face.

15" D.Fir S.44°W., 12.2 ft., healed face.

34" I.Cedar S.65°E., (S.76°E.) 68.6 ft. healed face.

20" D.Fir N.41°W., 4.0 ft., rotted stump, scribing visible, original.

NW BT missing, replaced

13" D.Fir, N.71°W., 21.9 ft. Blazed & scribed "T21S R6W S24 BT"

Set - 6' steel post 0.5' south