

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 689)

Set post cor. of secs. 7, 12, 13 and 18; from which
A Hemlock 7" dia., bears N.7°W., 50 lks. dist.
A Fir 6" dia., bears S.47°W., 37 lks. dist.
A Fir 24" dia., bears N.47°E., 8 lks. dist.
A Fir 24" dia., bears S.60°E., 11 lks. dist.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 699) (and page 829)

(Page 829)
(Finds cor. described as above)

(Page 699)
Where the cor. to secs. 7, 12, 13 and 18 stood. Reestablished the same by setting post 6" dia., 4 ft. long, with marked stone 12" in ground, marked T21S S7 on NE.; R5W S18 on SE.; R6W S13 on SW.; S12 on NW. face, with 4 notches on S. and 2 on N. edge; from which
Fir 35" dia., bears N.47°E., 8 lks. dist. mkd. T21S R5W S7 BT.
Fir 27" dia., bears S.54°E., 16 lks. dist. mkd. T21S R5W S18 BT.
Fir 10" dia., bears S.49°W., 47 lks. dist. mkd. T21S R6W S13 BT.
Cedar 18" dia., bears N.75°W., 35 lks. dist. mkd. T21S R6W S12 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C. Putnam, crew - Dec. 1961 - C.S. 49/89-7

Found - Cedar tree, 24" N.75°W., 23.1 ft., scribing visible on badly burned and rotted old face, "T2S."
Fir stump now 40", N.47°E., 5.3 ft., no scribing found, but old axe marks give appearance of having been smoothed off for bark scribing.
Fir stump now 34", S.54°E., 9.4 ft., not 10.6 ft., scribing visible on old face which has been previously opened.
No trace of SW. tree.

(Cont. Next Page)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

<p>Set Brass cap at cor. mkd: County Surveyors Office T 21 S R6W <table border="1" style="display: inline-table; vertical-align: middle;"> <tr> <td>S 12</td> <td>S 7</td> </tr> <tr> <td>S 13</td> <td>S 18</td> </tr> </table> R5W 1961 New BTs- 36" D.Fir S.65°W., 30.2 ft. mkd. T21S R6W S13 CSBT 24" D.Fir West 42.9 ft. mkd. T21S R6W S12 CS BT. 16" D.Fir S.19°E., 47.1 ft. mkd. T21S R5W S18 CSBT. No trees available in NE. quad.</p>	S 12	S 7	S 13	S 18
S 12	S 7			
S 13	S 18			
<p>Douglas County Surveyors Office - Vernon "Ray" Tracy and crew -1965 - C.S. File 54/14-9 ----- Found - DCSO brass cap. Orig. 24" Cedar N.75°W., 23.1 ft. Orig. 40" Fir stump N.47°E., 5.3 ft. Orig. 34" Fir stump S.54°E., 9.4 ft. Also found BTs recorded in 1961 New BT - 7" Chinquapin N.78°E. 19.9 ft. mkd. T21S R5W S7 CSBT</p>				
<p>Fd. & used on BLM Dependent resurvey by Lance J. Bishop & Wayne Rogers, Cadastral Surveyors, under Group #1158, surveyed Oct. 1983 - (DCSO records Vol. 47 Page(s) 17814) Fd. OK, July 1989 by D. Peel - M 108-55</p>				
<p>Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Oct. 29, 1991 - C.S. file 64/21-1 ----- Found - 1961 DCSO cap on a 1¼" O.D. I.P., protruding 10" above ground. 18" now 29" dia. Cedar with a previously opened burnt blaze, no marks visible, bears N.75°W., 23.1 ft. Orig. BT. 35" now 33" dia.,, 8 ft. high rotted D.Fir stump with cruiser axe marks on bark, bears N.47°E., 6.3 ft. (Rec. 5.3 ft.) (Rec. dist. is a possible face measurement) Orig. BT 27" now 30" dia. 5 ft. high rotted D.Fir stump with a previously opened blaze, scribing visible "S18 T21S B" bears S.61½°E., 9.4 ft. (Rec. S.54°E., 9.4 ft.) Orig. BT. 7" now 8" dia. dead Chinquapin with a previously opened rotted blaze, scribing visible "T21S R5W" bears N.78°E., 19.9 ft. (agrees w/rec) (1965) 16" now 27" dia. D.Fir with a fully healed double blaze, bears S.21°E., 47.1 ft. (Rec. S.19°E., 47.1 ft.) (1961) (Cont. Next Page)</p>				

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T21-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

36" now 31" dia. barked 6 ft. high D.Fir stump with a galv. steel cap on top and a healed blaze, bears S.65°W., 30.2 ft. (agrees w/rec) (1961)
24" now 21" dia. barked 7 ft. high D.Fir stump with a galv. steel cap on top and a healed blaze, bears West 42.0 ft. ((1961) (agrees w/rec)
New BTs- 7" dia., D.Fir double blaze and scribed "T21S R5W S7 CS BT" bears N.87 3/4°E., 23.3 ft.
7" dia. Hemlock double blazed and scribed "T21S R6W S12 CS BT" bears N.73½°W., 13.4 ft.
Corner lies near the East edge of clear-cut.