

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 689)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Fir 5" dia., bears N.25°E., 10 lks. dist. A Dogwood 5" dia., bears N.33°W., 14 lks. dist.</p>
<p>GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 699)</p> <p>-----</p> <p>Qr. sec. cor. gone. Reestablished the same by setting post, 4" dia., 4 ft. long, with marked stone, 12" in ground, mkd. ¼ S on W. face; from which Fir 8" dia., bears N.25°E., 10 lks. dist. mkd. ¼ S BT. Dogwood 6" dia., bears N.30°W., 14 lks. dist. mkd. ¼ S BT</p>
<p>Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy, Vernon Tracy & Clete Putnam, crew - Dec. 1961 - C.S. File 49/89-41</p> <p>-----</p> <p>Found - 8" Fir, down and nearly rotted away, N.25°E., 6.6 ft., cut open pitchy scar and found good reverse scribing "¼S". No trace of NW. BT found. Set Brass cap at cor. mkd: County Surveyors Office T 21 S R6W ¼ S12 S7 R5W 1961</p> <p>Old scribed stake mkd. "¼S" on N.; "S7" on E.; "S12" on W.; and "¼S" on S. faces, bears N.25°E., 2.6 ft. from corner. New BTs- 16" Hemlock S.87°E., 19.2 ft. mkd. ¼ S7 CS BT. 32" Hemlock S.71°W., 18.2 ft. mkd. ¼ S12 CS BT.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/21/2001 - C.S. File 66/21-38</p> <p>-----</p> <p>Found - 1961 DCSO brass cap/iron pipe, protrudes 13" out of ground. OBTs now gone. 32" now 29" dia., 35 ft. high Hemlock snag with a partially healed double blaze illegible scribing visible bears S.71°W., 18.2 ft. (1961) 16" now 21" dia., Hemlock with a fully healed double blaze bears S.87°E., 19.2 ft. (1961)</p> <p>New - 11" dia., D.Fir double blazed & scribed "¼ S12 CS BT" bears N.56°W., 13.2 ft. <u>continued next pg.</u></p>

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 12; & S. 7, T21-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

14" dia., Hemlock double blazed & scribed "¼ S12 CS
BT" bears S.61½°W., 28.4 ft.
10" dia., Hemlock double blazed & scribed "¼ S7 CS
BT" bears N.28½°E., 18.3 ft.
Compass decl. 17¾°E.