

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & S. 6, T21-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 689)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears S.83°E., 8 lks. dist.  
A Fir 8" dia., bears N.37°W., 11 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 8, 1958 - C.S. File 49/89-22

-----  
Found - Rotted snag, S.83°E., 5.3 ft., now approx. 15" dia. Found old scars and after chopping in, find evidence of old faces, (definitely made by axe) but no sign of any scribing.

Fir tree, now 22" dia. N.37°W., 7.3 ft. This tree had been chopped open previously (upper blaze), and the face burned so badly that nothing could be seen on it. Cut open lower blaze, found old face definitely made by axe, but only one straight scribe marks. Cut open top of upper blaze and found partial scribe marks above burned portion. Ring count shows face to have been made approx. 100 years ago.

Set Iron pipe with brass cap at cor. mkd:  
County Surveyor Office  
R6W ¼ S1|S6 R5W  
1958

New BTs- 4" D.Fir bears S.54½°E., 16 ft.  
22" D.Fir bears N.32°W., 17 ft.

Fd. OK, June 1965 plus 2 BLM BTs. C.S. File 53/101

BLM Resurvey by Norman J. McDonald, Survey Technician, under Group #469, Surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13088)

-----  
The ¼ sec. cor. which has been perpetuated with a DCSO marker, an iron post, 1" dia., protruding 8" from the ground, firmly set, with brass cap mkd. in 1958, from which the original bearing trees:

A rotted Fir snag, bears S.83°E., 8 lks. dist., with no marks visible.

A Fir 24" dia., bears N.37°W., 11 lks. dist., with fragmentary scribe marks visible on opened blaze. trees mkd. by the County:

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & S. 6, T21-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 18" dia., bears N.33°W., 26 lks. dist. mkd. ¼ S1 CS BT.  
A Fir 6" dia., bears S.55 3/4°E., 24 lks. dist., mkd. ¼ S6 CS BT.  
and new bearing trees:  
A Fir 9" dia., bears S.71°E., 93 lks. dist. mkd. ¼ S6 BT.  
A Fir 36" dia., bears S.12°W., 132 lks. dist. mkd. ¼ S1 BT  
I stamp USBLM 1962 on brass cap.

Fd. OK, May 1987 by R. Geisler - M 104-14  
Found OK by D. Edwards, Aug. 2000 - CS65/029-4