

PRIMARY CORNER DESCRIPTION Sec. cor. for 30 & 31; 25 & 36, T21-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 559)

Set post 4" dia., 4 ft. long, 24" in ground for cor. to secs. 25, 30, 31 and 36, mkd. T21S S30 on NE.; R7W S31 on SE.; R8W S36 on SW.; S25 on NW. faces, with 5 notches on N. and 1 on S. edge; from which
A Fir 7" dia., bears N.77°E., 17 lks. mkd. T21S R7W S30 BT
A Fir 7" dia., bears S.57°E., 9 lks. mkd. T21S R7W S31 BT.
A Fir 4" dia. bears S.13°W., 200 lks. mkd. T21S R8W S36 BT
A Fir 24" dia. bears N.25°W., 73 lks. mkd. T21S R8W S25 BT

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12549-50)

Point for the sec. cor. on line of old blazes N. and S.; determined from the remaining evidence:

A Fir stump bears N.25°W., 73 lks. dist., showing evidence of axe marks on SE. face.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

T 21 S
R 8 W | R 7 W
S 25 | S 30
S 36 | S 31
1952

from which

A Fir 26" dia. bears N.74¼°E. 81 lks. mkd. T21S R7W S30 BT
A Fir 12" dia. bears S.14°E., 45 lks. mkd. T21S R7W S31 BT
A Fir 12" dia. bears S.65½°W. 46 lks. mkd. T21S R8W S36 BT
A Fir 23" dia., bears N.60°45'W., 96 lks. mkd. T21S R8W S25 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21628)

The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54

A fir, 38" dia., bears N.74¼°E., 53.5 ft. no marks visible
A decayed fir stump, 20" dia., bears S.65½°W., 29.7 ft., no marks visible. (Record, 30.4 ft.)
A fir, 40" dia., bears N.60¾°W., 63.4 ft., with a healed blaze.
continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. cor. for 30 & 31; 25 & 36, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees

A fir, 9" dia. bears S.64°E., 41.1 ft mkd. T21S R7W S31 BT

A fir, 6" dia., bears S.62¾°W., 33.5 ft., mkd. T21S R8W
S36 BT.

Fd. & used on Dependent resurvey by Edith M Forkner,
Cadastral Surveyor, under Group #2115, surveyed January/May
2007 (DCSO records Vol. 56 Page(s) 22053)