

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 559-560)

Set post 4" dia., 4 ft. long, 24" in ground for qr. sec. cor. mkd. $\frac{1}{4}$ S on W. face; from which
A Laurel 5" dia., bears S.20°E., 13 lks. dist. mkd. $\frac{1}{4}$ S BT
A Dogwood 4" dia., bears S.72°W., 118 lks. dist. mkd. $\frac{1}{4}$ S BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12550)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:
 $\frac{1}{4}$
S 25 | S 30
1952

from which
A Fir 22" dia., bears N.66°E., 12 lks. dist. mkd. $\frac{1}{4}$ S30 BT.
A Fir 30" dia., bears S.62°45'W., 12 lks. dist. mkd. $\frac{1}{4}$ S25 BT.
On nearly level course along a ravine.

Fd. OK, May 30, 1982 by L. Roberts - M 90-21

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21629)

The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.
from which the bearing trees mkd. by Lytle, et al. in 1952-54
A fir, 30" dia. bears N.66°E., 7.9 ft. with a healed blaze
A fir, 41" dia. bears S.62 $\frac{3}{4}$ °W. 7.9 ft. with a healed blaze
An iron rod with an International Paper Co. sign is alongside the cor.
Corner is located E 50 ft of creek, 2 ft wide, course S.10°W.