

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T21-8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 561-62)

 Set stake 4" dia., 4 ft. long, 24" in ground for cor. to secs. 7, 12, 13 and 18, marked T21S S7 on NE.; R7W S18 on SE.; R8W S13 on SW.; S12 on NW. faces, with 4 notches on S. and 2 on N. edge; from which

A Hemlock 32" dia., bears N.15°E., 18 lks. dist. mkd. T21S R7W S7 BT.

A Hemlock 8" dia., bears S.7°E., 37 lks. dist. mkd. T21S R7W S18 BT.

A Maple 10" dia., bears S.25°W., 34 lks. dist. mkd. T21S R8W S13 BT.

A Maple 12" dia., bears N.73°W., 18 lks. dist. mkd. T21S R8W S12 BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12553-54)

 Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

T	21	S		
R	8	W	R	7
			S	7
S	12		S	18
			S	13
1954				

from which

A Hemlock 13" dia., bears N.48°E., 30 lks. dist. mkd. T21S R7W S7 BT.

A Hemlock 10" dia., bears S.58°E., 38 lks. dist. mkd. T21S R7W S18 BT.

A Fir 38" dia., bears S.56½°W., 21 lks. dist. mkd. T21S R8W S13 BT.

A Hemlock 8" dia., bears N.59½°W., 29 lks. dist. mkd. T21S R8W S12 BT.

Douglas Co. Surveyors Office - L.E. Monrean; P.L. Earle, crew - Oct. 29, 1975 - C.S. File 57/36-24

 Found - GLO 1954 brass cap, properly marked.
 13" now 15" dia. Hemlock stump, bears N.48°E., 19.0 ft. (Rec. 19.8 ft.) has good blaze.
 10" now 11" dia. Hemlock stump, bears S.58°E., 24.2 ft. (Rec. 25.1 ft.) has good blaze.
 38" Fir stump, bears S.56½°W., 13.9 ft., has good blaze. (Cont. Next Page)

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" now 12" Hemlock stump, bears N.59½°W., 19.7 ft.
(Rec. 19.1 ft.) I open portion of blaze and find
good scribing "S12 BT"
Bark has been removed from all bearing tree stumps and a
preservative has been applied. Stumps have been capped with
alum. sheet metal and are tagged.
New Accessory:
A Cedar 7½" dia., bears S.27½°W., 45.6 ft. scribed
"T21S R8W S13 CS BT". Tree is growing out from
the N NE. side of 52" dia. Fir stump . Large
blaze is 5 ft. above ground, bearing and distance
were recorded from the height described.
No other BTs were scribed as corner lies in clear cut area.