

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for S. 7; & 12, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 562)

Set post 4" dia., 4 ft. long, 24" in ground for qr. sec. cor. mkd. ¼ S on W. face; from which

A Hemlock 6" dia., bears S.70°W., 65 lks. dist. mkd. ¼ S BT.

A Hemlock 5" dia., bears S.65°E., 28 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12554)

The ¼ sec. cor., determined from the remaining original bearing tree as follows:

A fallen Hemlock 16" dia., bears S.65°E., 28 lks. dist. mkd. ¼ S on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 12 | S 7
1954

from which new bearing trees:

A Hemlock 17" dia., bears S.71¼°E., 28 lks. dist. mkd. ¼ S7 BT.

A Hemlock 14" dia., bears S.75°45'W., 22 lks. dist. mkd. ¼ S12 BT.

Fd. OK, July 1981 by L. Roberts - M 88-22

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2720, surveyed Aug./Oct. 2013 - (DCSO records Vol. 58 Page(s) 23116)

The ¼ sec. cor. of secs. 7 & 12, on the W. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remains of a BT mkd. by Lytle, et al, in 1952-54

A decayed hemlock stump, size indeterminate, bears S.75¾°W., 14.5 ft. with no marks visible.

and new bearing trees

A fir, 13" dia., bears N.38½°E., 23.7 ft., mkd. ¼ S7 BT.

A hemlock, 16" dia. bears N.42¾°W., 14.2 ft. mkd. ¼ S12 BT