

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 562)

-----  
Set post 4" dia., 4 ft. long, 24" in ground for cor. to secs. 1, 6, 7 and 12, marked T21S S6 onNE.; R7W S7 on SE.; R8W S12 on SW.; S1 on NW. faces, with 1 notch on N. & 5 on S. edges, from which

- A Hemlock 5" dia., bears N.30°W., 23 lks. dist. mkd. T21S R8W S1 BT.
- A Hemlock 8" dia., bears N.60°E., 50 lks. dist. mkd. T21S R7W S6 BT.
- A Hemlock 6" dia., bears S.65°E., 11 lks. dist. mkd. T21S R7W S7 BT.
- A Fir 40" dia., bears S.64°W., 33 lks. dist. mkd. T21S R8W S12 BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12555)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 21 S  
R 8 W R 7 W  
S 1 S 6  
S 12 S 7  
1954

from which

- A Fir 22" dia., bears N.11°E., 12 lks. dist mkd. T21S R7W S6 BT.
- A Fir 27" dia., bears S.1½°E., 34 lks. dist. mkd. T21S R7W S7 BT.
- A Fir 18" dia., bears S.5°W., 11 lks. dist. mkd. T21S R8W S12 BT.
- A Fir 25" dia., bears N.56½°W., 69 lks. dist. mkd. T21S R8W S1 BT.