TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 6 of T22-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 633)

Set ¼ sec. post, from which
A Fir 20" dia., bears N.49°W., 48 lks. dist.
A Fir 48" dia., bears S.37°W., 64 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and M.Stone, crew - Aug. 3, 1962 - C.S. File 52/14-94

Found - Fir, now 40", N.49°W., 31.7 ft., very faint bark scribing visible "S" and part of "B".
Fir snag bears S.37°W., 42.2 ft., bark all gone and big hole burned in NE side. No marks found.
Set Brass cap at cor. mkd: County Surveyors Office

¼ $\frac{\text{S 31}}{\text{S 6}}$ T21S / T22S R7W

1962

New BTs -16" D.Fir N.75°E., 10.2 ft. mkd. ¼ S31 CS BT.
10" D.Fir South, 31.6 ft. mkd. ¼ S6 CS BT.

Cor. Fd. and used in BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 536, surveyed May/June 1964 (DCSO records Vol. 32 Page(s) 13511-12)

BLM resurvey by Michael O. Jones, Cadastral Surveyor under special instructions dated May 27, 2009 - Surveyed June/Aug. 2009 - (DCSO records BLM plat 2011 & Vol. 56 Page 22266)

The ¼ sec. cor. of secs. 6 & 31 on the N. bdy. of the Tp., perpetuated by Godfrey, in 1962, and accepted by Brooks and Jelley in 1964; monumented with an iron pipe, 1½" dia., firmly set, projecting 11" above ground, with a brass cop (properly) mkd.
from which the remains of the original BTs
A hollow burnt fir snag, 25" dia., bears S.34°W., 42.2 ft no marks visible. (Record. S.37°W.)
A fir, 47" dia., bears N.49°W., 31.7 ft., with an X in bark at head height and a hack in bark at waist height.
and BTs by Godfrey and reported by Brooks and Jelley
A fir, 31" dia. bears N.75°E., 10.2 ft with a healed blaze
A fir, 26" dia., bears South, 31.7 ft., no marks visible.