TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 668)

---

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 40" dia., bears N.30°W., 33 lks., mkd: ¼ S BT.
Fir, 36" dia., bears S.10°E., 48 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13523)

---

Point for ¼ sec. cor. of secs. 30 & 31, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼ S 30
S 31
T 21 S R 7 W
1964

from which
A W.Fir, 20" dia., bears N.53½°W., 64½ lks. mkd: ¼ S30 BT.
A Cedar, 72" dia., bears S.63°E., 66 lks., mkd: ¼ S31 BT.

Fd. Ok by L. Roberts, 5/30/1982 - M 90-21

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21641)

---

The ¼ sec. cor. of secs. 30 and 31, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
from which a bearing tree mkd. by Brooks and Jelley in 1964
A cedar, 77" dia., bears S.63°E., 43.6 ft., with a healed blaze.
and a new bearing tree
A fir, 16" dia., bears N.8½°E., 59.6 ft., mkd. ¼ S30 BT. Tree is located on top of the N. cutbank of overgrown graveled road, 15 ft. wide, bears N.80°W. and S.80°E.