

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION W C 1/4 Cor Secs 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 674)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked 1/4 S on N face; from which
Fir, 50" dia., bears S.30°E., 23 lks., mkd: 1/4 S BT.
Cedar, 20" dia., bears N.40°E., 42 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Donald R. Beck, Cadastral Surveyor, under group #655, surveyed Sept./Oct. 1967 - (DCSO records Vol. 34 Page(s) 14167)

The 1/4 sec. cor. of secs. 7 & 18 determined at the record bearing & distance from the orig. BT:

A cedar 37" dia., bears N.40°E., 42 lks., with scribe marks 1/4 S visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap marked:

T21S R7W
1/4 S 7
S 18
1967

from which

An Alder, 8" dia., bears S.47°W., 72 lks., mkd: 1/4 S18 BT.

Douglas Co. Surveyors Office - Franklin W. Jones - Willie Penley - 1/7/1970 - C.S. File 56/12-2

Witness corner to 1/4 cor. Secs. 7 & 18

Found - BLM 1967 brass cap, plus 2 good BTs (our office doesn't have notes for this corner (unapproved) at this time, we used the brass cap & tags on each BT)

8" Alder S.47°W., 47.5 ft. found bark scribing, tagged in 1967

36" Cedar N.33°E., 27.7 ft. (1954 tag said N.40°E.) found scribing to be 33 years old (ring count) on opened face.

Note - We were asked to move this corner as it falls in proposed logging rd. No. 21-7-15-1. We set witness corner 145 ft. N of 1/4 corner. Removed brass cap & reset & remarked. In place where 1/4 cor., set 5/8" iron rod.

Reset brass cap at wit. cor. mkd: US Dept. of the Interior

T21S R7W S 7
W C 145.0 ft. South to 1/4 S 18
1967

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION W.C. 1/4 Cor. Secs. 7 & 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs- 12" Hemlock S.18½°W., 15.2 ft., mkd: WC ¼ S7 CS BT
40" Hemlock N.76°W., 27.2 ft., mkd: WC ¼ S7 CS BT
Note - Found no stationing good enough to tie Wit. Cor. to
at this time as they have set everything other
than old P. Line stakes & R/W markers years
before.