

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 166700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T20-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 575)

-----  
Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 31 & 32, marked T20S R7W on N.; S32 on E.; S31 on W. faces, with 5 notches on E. & 1 notch on W. face; from which  
A Fir 24" dia., bears N.35°E., 14 lks. dist. mkd. T20S R7W S32 BT.  
A Fir 22" dia., bears S.81°W., 42 lks. dist. mkd. T20S R7W S31 & 32 BT.  
A Fir 16" dia., bears N.4°W., 33 lks. dist. mkd. T20S R7W S31 BT.

-----  
Wilford N. Haines, #239 - For: Woolley Logging Co. - 1961 - C.S. File 51/222 and M 21-76

-----  
Found original bearing trees.  
Set 1" x 1" x 36" T. Iron.

-----  
Survey by Donald L. Branch - For: International Paper Co. - Nov. 1983 - M 95-66

-----  
Found - T-Iron with cap mkd. "Survey Marker Haines Drain OR. 36" Fir stump bears N.35°E., 9.0 ft. with no scribing.  
Burnt out stump with no visible markings, bears S.81°W, 27.7 ft.  
Set standard International Paper Co. 2½" I.D. alum. pipe protruding 6" above ground with ¾" alum. pipe mkd. "T20S R7W S31 S32 T21S R7W S6 1983 PLS 1137".  
New Accessories:  
36" D.Fir bears S.16°W., 54.7 ft. scribed T21S R7W S6 BT.  
Set ½" x 6 ft. rebar, 30" in ground with BT sign attached, bears N.63°W., 10.8 ft.  
5/8" x 30" rebar with 1¼" yellow plastic cap mkd. "Branch Eng. LS 1137" in top of BT stump, bears N.35°W., 9.0 ft.