TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 666)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 40" dia., bears S.70°W., 33 lks., mkd: ¼ S BT.
Cedar, 30" dia., bears N.41°E., 200 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13520)

Point for ¼ sec. cor. of secs. 31 & 32, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 31|S 32
T 21 S R 7 W
1964

From which
A Cedar, 17" dia., bears N.21°E., 33 lks., mkd: ¼ S32 BT.
A Cedar, 10" dia., bears N.24¼°W., 15½ lks. mkd: ¼ S31 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21636)

The ¼ sec. cor. of secs. 31 and 32, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.
from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964
A cedar stump, 27" dia., bears N.21°E., 21.8 ft., no marks visible.
A roothole bears N.24¼°W., 10.2 ft., with a down cedar, 9" dia., alongside, no marks visible.
and new bearing trees
A fir, 6" dia., bears S.86½°E., 3.4 ft., mkd. ¼ S32 BT.
A fir, 7" dia., bears N.52¼°W., 5.1 ft., mkd. ¼ S31 BT.