

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 666-7)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 29, 30, 31, & 32, mkd. T 21 S S 29 on NE, R 7 W S 32 on SE, S 31 on SW, S 30 on NW face, with 5 notch(es) on E & 1 on S edges; from which
Fir, 36" dia. bears N.14°W., 64 lks. mkd: T21S R7W S30 BT.
Fir, 18" dia. bears N.27°E., 58 lks. mkd: T21S R7W S29 BT.
Fir, 8" dia. bears S.48°W., 52 lks. mkd: T21S R7W S31 BT.
Fir, 4" dia., bears S.27°E., 74 lks. mkd: T21S R7W S32 BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13520-1)

The cor. of secs. 29, 30, 31, & 32, determined at the record bearing & dist. from each of the remaining orig. BTs:

A Fir, 38" dia., bears N.27°E., 58 lks., with no marks remaining on scaled bark blaze.

A Fir, 54" dia., bears N.14°W., 64 lks., with fragmentary scribe marks visible on badly scaled bark blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T21S	R7W
S 30	S 29
S 31	S 32
1964	

from which new BTS

A Fir, 10" dia. bears N.35°E. 10 lks. mkd: T21S R7W S29 BT

A Fir, 16" dia. bears S.53°E. 33 lks. mkd: T21S R7W S32 BT

A Fir, 5" dia. bears S.27°W. 14½ lks. mkd: T21S R7W S31 BT

A Fir, 5" dia. bears N.21°W. 56 lks. mkd: T21S R7W S30 BT.

Douglas Co. Surveyors Office - John M. Powell - G. Commons - May 10, 1973 - C.S. File 56/25-18

Found - 1964 BLM brass cap out of ground.
Orig. BT 38" D.Fir, N.27°E., 38.3 ft. As noted no marks remain.

10" D.Fir now 12" N.35°E., 6.6 ft. shows good scar.
16" D.Fir now 19" S.47°E., (rec. S.53°E.) 19.4 ft. (rec. 21.8 ft.) this tree has undoubtedly slid down hill.

SW & NW BTs gone.

Renewal- Using orig. BT & the NE BT, I reset 1964 BLM brass cap at cor. which is at the top of slide.

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - Witness cor. mkd: County Surveyors Wit. Cor. 36' W to
Office T21S R7W
1973 S30|S29
S31|S32

New BTs- 25" D.Fir N.48°E. 22.7 ft. mkd:T21S R7W S29 WC CS BT
8" Chinquapin" N.4°E., 14.1 ft. mkd: T21S R7W S29 WC
CS BT

Dependent resurvey by Edith M Forkner, Cadastral Surveyor,
under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCS0
records Vol. 55 Page(s) 21637-8)

Point for the cor. of secs. 29, 30, 31, and 32, determined at
record bearing and distance from the witness corner
established by the Douglas County Surveyor in 1973,
monumented with an iron post, 1" dia., firmly set, projecting
18" above ground, bears East, 36.00 ft., with brass cap mkd.

W.C. 36 W. TO
T 21 S R 7 W
S 30|S 29
S 31|S 32
1973

from which the bearing trees mkd. by the Douglas County
Surveyor in 1973

A chinquapin, 16" dia., bears N.8¾°E., 14.1 ft., with a
healed blaze.

A fir, 32" dia., bears N.56½°E., 21.9 ft., with a healed
blaze.

The 1964 iron post set by Brooks and Jelley was found lying
loose on the surface of the ground.

At the Corner Point

Reset 1964 iron post, 28 ins. long, 2 1/2" dia., 28 ins. in
the ground, with brass cap mkd.

T 21 S R 7 W
S 30|S 29
S 31|S 32
1964

from which an original bearing tree

A fir, 41" dia., bears N.27°E., 38.3 ft., with a healed
blaze at breast height.

and the remains of the bearing trees mkd. by Brooks and
Jelley in 1964, which are on an unstable slump on top of a
cut bank

A fir, 22" dia., bears N.25¾°E., 8.1 ft., with a healed
blaze. (Record, N.35°E., 6.6 ft.)

A decayed fir stump, size indeterminate, bears S.50¾°E.,
17.8 ft., no marks visible. (Rec. S.53°E., 21.8 ft.)

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees
A fir, 14" dia., bears S.7¼°E., 54.8 ft., mkd. T21S R7W S32 BT.
A fir, 29" dia., bears S.12¼°W., 60.5 ft., mkd. T21S R7W S31 BT.
A fir, 13" dia., bears N.50½°W., 68.6 ft., mkd. T21S R7W S30 BT. Tree is located on the W. edge of overgrown graveled road, 20 ft. wide, bears N.10°E. and S.10°W.
Deposit a magnet in a white plastic case at the base of the iron post.
Corner is located just below the top of a steep road cutbank, bears W., and partly under the roots of the NE. bearing tree mkd. by Brooks and Jelley in 1964.