

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 668)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked  $\frac{1}{4}$  S on N face; from which  
Cedar, 30" dia., bears S.50°W., 33 lks., mkd:  $\frac{1}{4}$  S BT.  
Fir, 40" dia., bears N.10°E., 63 lks., mkd:  $\frac{1}{4}$  S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13524)

-----  
Point for  $\frac{1}{4}$  sec. cor. of secs. 29 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, with brass cap marked:  
 $\frac{1}{4}$   
S 30 | S 29  
T 21 S R 7 W  
1964

from which  
A fir, 22" dia., bears N.68 $\frac{1}{4}$ °E., 33 lks., mkd:  $\frac{1}{4}$  S29 BT.  
A fir, 22" dia., bears S.9 $\frac{1}{2}$ °W., 110 lks., mkd:  $\frac{1}{4}$  S30 BT.

Fd. Ok by L. Roberts, 5/30/1982 - M 90-21

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21643-4)

-----  
The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, monumented with an iron post, 2 $\frac{1}{2}$ " dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.  
from which the bearing trees mkd. by Brooks & Jelley in 1964  
A fir, 31" dia., bears N.68 $\frac{1}{4}$ °E., 21.8 ft., with a healed blaze.  
A fir, 31" dia., bears S.9 $\frac{1}{2}$ °W., 72.6 ft., with a healed blaze.