

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 668-9)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 19, 20, 29, & 30, mkd. T 21 S S 20 on NE, R 7 W S 29 on SE, S 30 on SW, S 19 on NW face, with 5 notches on E & 2 on S edges; from which
 Fir, 24" dia. bears N.50°E., 77 lks. mkd: T21S R7W S20 BT.
 Fir, 30" dia. bears N.13°W., 130 lks. mkd: T21S R7W S19 BT
 Fir, 40" dia., bears S.3°E., 30 lks. mkd: T21S R7W S29 BT.
 Fir, 40" dia. bears S.40°W., 56 lks. mkd: T21S R7W S30 BT

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13525)

The cor. of secs. 19, 20, 29, & 30, determined at the record bearing & dist. from the orig. BTs:
 A burned & decayed fir stump, 15" dia., bears N.50°E., 67 lks., with no marks remaining. (Rec. dist. 77 lks.)
 A burned & decayed fir snag, 50" dia., bears S.3°E., 30 lks., with no marks remaining.
 A decayed fir snag, 45" dia., bears S.40°W., 56 lks., with scribe marks S30 T21S R7W BT visible on bark blaze.
 A burned & decayed fir stump, 20" dia., bears N.13°W., 130 lks., with no marks remaining.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
 T21S R7W
 S 19 | S 20
 S 30 | S 29
 1964

from which new BTs
 A fir, 36" dia. bears N.5°E. 61½ lks. mkd: T21S R7W S20 BT
 A fir, 7" dia. bears S.54°E. 61½ lks. mkd: T21S R7W S29 BT
 A fir, 28" dia. bears S.53°W., 107 lks., mkd: T21S R7W S30 BT.
 A fir, 10" dia., bears N.15°W., 108 lks., mkd: T21S R7W S19 BT.

Fd. & used on BLM dependent resurvey by Donald R. Beck, Cadastral Surveyor, under group #655, surveyed Sept./Oct. 1967 - (DCSO records Vol. 34 Page(s) 14159)

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21646-7)

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A burned decayed fir snag, 46" dia., bears S.3°E., 21.4 ft., no marks visible. (Record, 19.8 ft.)

A roothole with bark and decayed fir remains bears S.40°W., 37.0 ft., no marks visible.

A roothole with bark and decayed fir remains bears N.13°W., 85.8 ft., no marks visible.

and the remains of the BTs mkd. by Brooks and Jelley in 1964

A fir stump, 40" dia., bears N.5°E., 40.6 ft., with a healed blaze.

A fir, 44" dia., bears S.56½°W., 70.6 ft., with a healed blaze. (Record, S.53°W.)

A fir, 10" dia., bears N.15°W., 71.3 ft., with a healed blaze.

and new bearing trees

A fir, 6" dia. bears N.83°E., 61.4 ft mkd. T21S R7W S20 BT

A fir, 24" dia., bears S.65¾°E., 68.1 ft., mkd. T21S R7W S29 BT.

A rebar with IP Co. property sign is alongside the cor.

Corner is located on SW. cor. of fir reproduction, edge bears N. and E., and NE., 25 ft. of drainage, course N.50°W.