TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 670)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 40" dia., bears N.78°W., 20 lks., mkd: ¼ S BT.
Fir, 20" dia., bears N.35°E., 56 lks., mkd: ¼ S BT.

BLM dependent resurvey by Donald R. Beck, Cadastral Surveyor, under group #655, surveyed Sept./Oct. 1967 - (DCSO records Vol. 34 Page(s) 14162)

The ¼ sec. cor. of secs. 19 & 20 determined at the record bearing & distance from the remains of the orig. BTs:
A stump hole, bears N.35°E., 56 lks.
A fir snag, 60" dia., bears N.78°W., 20 lks., mkd: ¼ S BT on bark blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked: T 21 S R 7 W

¼
S 19|S 20
1967

from which
A fir, 8" dia., bears S.36°E., 4 lks., mkd: ¼ S20 BT.
A fir, 12" dia., bears N.19½°W., 31½ lks., mkd: ¼ S19 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21648-9)

The ¼ sec. cor. of secs. 19 and 20, monumented with an iron post, 2½" diam., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A roothole bears N.35°E., 37.0 ft.
A fir snag, 44" dia bears N.78°W. 13.2 ft no marks visible and the bearing trees mkd. by Beck in 1967
A fir, 19" dia., bears S.36°E., 2.6 ft., with a healed blaze and snow blaze.
A fir, 22" dia., bears N.17°W., 20.8 ft., with a healed blaze. (Record, N.19½°W.)
A rebar with IP Co. property sign is alongside the cor.
Corner is located on NW. cor. of fir reproduction, edge bears S. and E.