

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 676)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which  
Fir, 12" dia., bears N.80°W., 9 lks., mkd: ¼ S BT.  
Fir, 14" dia., bears S.80°E., 10 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - Oct. 1962 - C.S. File 49/20-16

-----  
Found - 4" sq. wooden stake at corner. - The fir S.80°E., 6.6' is down, dead & burned, also bulldozed out of position. Part of old face exposed & mks. burned off. Chop open & find good scribe on upper edge of old face. Tag on tree dated same date & name as on stake at cor. Portion of root in gr. that checks bear & dist. from corner.

No trace of NW BT. Entire area around corner logged off and burned, fire trail on both East & West of corner.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962  
T21S R7W ¼ S6/S5

New BTs- 10" Hemlock S.69½°W., 53.7 ft. mkd: ¼ S6 CS BT  
11" Hemlock S.30½°W., 84.1 ft. mkd: ¼ S6 CS BT  
No trees available East of corner.

Les Roberts - For: Int. Paper Co. - June 15, 1982 - M92-37

-----  
Found - 1962 Doug. Co. BC  
17" Hemlock bears S.30°W. 83.7 ft (Scar visible)1962  
18" Hemlock bears S.69°W. 53.7 ft (Scar visible)1962

New BT - 12" Fir bears S.73°E., 21.3 ft. (scribed)

Ron Rice, NW Land Surveying - Jason Collver - Sept. 2012 - C.S. File 65/77-41

-----  
Found - 1962 Doug. Co. BC  
17" Hemlock bears S.30°W. 83.7 ft (Scar visible)  
1962 Fd 23" Hem with healed face 9-17-2012  
18" Hemlock bears S.69°W. 53.7ft (Scar visible) 1962  
Fd 24" Hemlock with healed face 9-17-2012  
12" Fir bears S.73°E., 21.3 ft. (scribed Fd 25"  
D.Fir stump with rotted face 9-17-2012

New - 21" D.Fir bears S.6°E., 35.9 ft. scribed ¼ S5 BT  
20" D.Fir bears N.23°E., 19.6 ft. scribed ¼ S5 BT

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Corner has steel post adjacent to it. All BTs have  
red painted bands and yellow tags.  
Declination 16° East