

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 557-58)

Set post 6" dia., 4 ft. long, 24" in ground for closing cor. to secs. 5 & 6, marked T20S R7W S32 on N.; R7W S5 on SE.; T21S S6 on SW. face; with 1 notch on W. & 5 on E. edge; from which

- A Fir 36" dia., bears N.43°E., 35 lks mkd. T20S R7W S32 BT
- A Fir 36" dia., bears S.32°E., 27 lks mkd. T21S R7W S5 BT
- A Fir 40" dia., bears S.63°W., 25 lks mkd. T21S R7W S6 BT

Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 575)

Wilford Haines, filed Feb. 10, 1984 - C.S. File 58/290-1

About 30 yrs. ago I went with Ernie Black & another man from BLM to the corner of sects. 5 & 6, T21S R7W WM on the south line of sec. 32, for the purpose of renewing this corner. They showed me one BT which was down & in area to be burned. They were afraid that the corner would be lost, so with their help I set one of my "T" irons for the corner.

Survey by Donald L. Branch, LS #1137 - For: International Paper Co. - Nov. 1983 - M 95-66

Found - "T" Iron, no record, with cap mkd. "Survey Marker W. Haines Drain OR"

At the same point and with the T iron inside, SET a 2½" alum. pipe, protruding 6" above ground with standard International Paper Co. ¾" alum. cap mkd. "T20S R7W S32 S6 S5 T21S R7W 1983 PLS 1137".

New BTs- 16" D.Fir bears N.3°E., 33.7 ft. scribed T20S R7W S32 BT.

17" Chinquapin bears S.32°W., 5.8 ft. scribed T21S R7W S6 BT.

18" D.Fir bears S.25°E., 43.6 ft. scribed T21S R7W S5 BT.

Ron Rice, NW Land Surveying - Jason Collier - Sept. 12, 2012 - C.S. File 65/77-40

Found - 2½" alum. pipe, protruding 6" above ground with standard International Paper Co. ¾" alum. cap mkd. "T20S R7W S32 S6 S5 T21S R7W 1983 PLS 1137".

16" D.Fir bears N.3°E., 33.7 ft. scribed T20S R7W S32 BT. (Fd 26" D. Fir with healed face)

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only (North)

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

	17" Chinquapin bears S.32°W., 5.8 ft. scribed T21S R7W S6 BT. (Fd 23" Chinquapin with healed face)
	18" D.Fir bears S.25°E., 43.6 ft. scribed T21S R7W S5 BT. (Fd 27" D. Fir with healed face)
New -	15" Chinquapin bears S.70°E., 6.3 ft, scribed T21S R7W S5 BT
Note -	Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags. Declination 16° East