

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32; & 5, T22-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 633)

Set ¼ sec. post, from which
A Fir 18" dia., bears S.10°E., 28 lks. dist.
A Fir 36" dia., bears N.53°E., 18 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 536, surveyed May/June 1964 (DCSO records Vol. 32 Page(s) 13510-11)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 21 S
 S 32
¼ S 5
T 22 S R 7 W
 1964

from which
A Fir 4" dia., bears N.45°W., 21 lks. dist. mkd. ¼ S32 BT
A Fir 5" dia., bears S.7°E., 41 lks. dist. mkd. ¼ S5 BT.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed May 2012 - DCSO records BLM Plat 2013-1, T22-7 and Vol. 58 Page(s) 22975

The ¼ sec. cor. of secs. 5 & 32, on the N. bdy. of the Tp., monumented with on iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which the BTs mkd. by Brooks and Jelley

A fir, 21" dia., bears S.7°E., 27.1 ft., with a healed blaze.
A fir, 33" dia., bears N.45°W., 13.9 ft., with a healed blaze.