

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 667)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Cedar, 40" dia., bears S.41°W., 13 lks., mkd: ¼ S BT.
Cedar, 36" dia., bears S.12°E., 41 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13521-2)

The ¼ sec. cor. of secs. 29 & 32, determined at intersection of the facing of an orig. BT & Wright's line from the west as indicated by a bark blaze on a burned fir snag about 6 chs. westerly from the corner. This position is substantiated by the position of the creek shown in Wright's notes as being 2.08 chs. east of the ¼ sec. corner & by the record dist. of the W ½ mile of this line. The BTs shown in the orig. field notes are actually those for the sec. cor. of secs. 32 & 33, which still exist at that corner. The BT south of the corner cannot be identified & may have been carried down hill in a slide. From the established corner point, the orig. BT:

A fir, 67" dia., bears N.35°W., 24 lks., with scribe marks
BT ¼ S visible on bark blaze. These marks are identical in style, size, & character to those found on other BTs marked by Wright in this area.

At the corner point

Set an iron post, 28" long, 2½" dia., 14" in the ground, to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap marked:

_____ ¼	<u>S 29</u>
	S 32
T 21 S R 7 W	
1964	

from which new BTs

A hemlock, 5" dia., bears N.41½°W., 35 lks. mkd: ¼ S29 BT.
A hemlock, 9" dia., bears S.28°W., 43 lks., mkd: ¼ S32 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21639)

The ¼ sec. cor. of secs. 29 and 32, determined at record bearing and distance from the remains of the original BT

A decayed fir stump, 52" dia., bears N.35°W., 15.8 ft., no marks visible.

and the bearing trees mkd. by Brooks and Jelley in 1964
continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A multi-top hemlock, 15" dia., bears S.28°W., 28.4 ft.,
with a healed blaze.

A half decayed live hemlock, 11" dia., bears N.32³/₄°W.,
25.9 ft., no marks visible. (Record, N.41¹/₂°W., 23.1
ft.)

At the Corner Point

Set an iron rod, 18" long, 5/8" dia., 6" in solid sandstone,
in a mound of dirt, 2 ft base, 8" high, with aluminum cap mkd

T 21 S R 7 W

S 29
1/4 S 32

2005

from which new bearing trees

A fir, 13" dia., bears N.57°E., 29.5 ft., mkd. 1/4 S29 BT.

A fir, 8" dia., bears S.11¹/₂°W., 8.9 ft., mkd. 1/4 S32 BT.

The 1964 iron post set by Brooks and Jelley was found lying
loose. Dispose of the 1964 iron post.