

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 669)

A Fir, 8" dia., for qr. sec. cor. marked ¼ S on N face: from which

Fir, 18" dia., bears N.30°E., 11 lks., mkd: ¼ S BT.

Fir, 30" dia., bears S.5°E., 32 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13526-7)

The ¼ sec. cor. of secs. 20 & 29 determined at the record bearing & distance from the orig. BTs, there is no evidence of the corner tree.

A fir, 30" dia., bears N.30°E., 11 lks., with fragmentary scribe marks visible on scaled bark blaze.

A down fir, 30" dia., bears S.5°E., 32 lks., with no marks remaining.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼ $\frac{S\ 20}{S\ 29}$

T21S R7W

1964

A fir, 16" dia., bears N.44¼°E., 75 lks., mkd: ¼ S20 BT.

A fir, 4" dia., bears S.72¾°E., 66½ lks., mkd: ¼ S29 BT.

Fd. Ok on BLM dependent resurvey by Donald R. Beck, Cadastral Surveyor, under group #655, surveyed Sept./Oct. 1967 - (DCSO records Vol. 34 Page(s) 14159)

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21645)

The ¼ sec. cor. of secs. 20 and 29, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir, 35" dia., bears N.30°E., 7.3 ft., no marks visible.

A roothole bears S.5°E., 21.1 ft., with a down fir, size indeterminate, alongside, no marks visible.

and the remains of the bearing trees mkd. by Brooks and Jelley in 1964

A fir stump, 18" dia., bears N.44¼°E., 48.7 ft., with a healed blaze. (Record, 49.5 ft.)

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 7" dia., bears S.72 $\frac{3}{4}$ °E., 43.9 ft., with a healed blaze.
A rebar with International Paper Co. property sign is alongside the cor. A BLM location tag is on a fir, 3 ft. diam., E., 25 ft.
Corner is located on S. edge of fir reproduction, edge bears E. and W.