

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 266700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T20-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 574)

Set Cedar post 4 ft. long, 4" sq., 24" in ground for cor. to secs. 32 & 33, marked T20S R7W on N.; S32 on W.; S33 on E. faces, with 2 notches on W. and 4 notches on E. faces; from which

A Cedar 10" dia., bears N.9°E., 25 lks. dist. mkd. T20S R7W S33 BT.

A Fir 12" dia., bears S.27°W., 19 lks. dist. mkd. T20S R7W S32 & 33 BT.

A Hemlock 18" dia., bears N.25°W., 45 lks. dist. mkd. T20S R7W S32 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - 1962 - C.S. File 49/89-36

Found - Haines' "T" Iron and cap, not recorded.
15" Fir snag, S.27°W., 12.5 ft. scribing visible "T21S R7W S5 BT".
No trace of NE. or NW. BTs.

Did not set brass cap.

New BTs- 6" Hemlock N.57½°E., 45.7 ft. mkd. S33 CS BT.

8" Hemlock N.58°W., 24.6 ft. mkd. T20S R7W S32 CS BT
Cor. lies on steep NW. slope approx. 500 ft. South of road.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1159, surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18039)

The Sec. cor., perpetuated by Haines, subsequently perpetuated and recorded by Godfrey in 1962, monumented with a 1" "T" shaped iron rod, firmly set, projecting 4" above ground, from which the remains of an original bearing tree:

A decayed Fir stump, size indeterminate, bears S.27°W., 19 lks. dist., no marks visible.

and bearing trees mkd. by Godfrey:

A Hemlock 12" dia., bears N.57½°E., 69 lks. dist., with healed double blaze.

A Hemlock 12" dia., bears N.58°W., 37½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron rod, with brass cap mkd: T 20 S R 7 W

S 32 | S 33

S 5

T 21 S R 7 W

cont.

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 266700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T20-7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

BLM Dependent Retracement by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed May 2012 - DCSO records BLM Plat 2013-1, T20-7 & Vol. 58 Page(s) 22950

The cor. of secs. 32 & 33, on the S. bdy. of the Tp., monumented with on iron post, 2½" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Godfrey, in 1962

A sawed hemlock stump, 10" dia., bears N.57½°E., 45.5 ft., with a healed blaze.

A hemlock, 17" dia., bears N.58°W., 24.8 ft.. with a healed blaze.

and new bearing tree

A fir, 4" dia., bears N.48¼°E., 33.4 ft., mkd. X BT.

Latitude 43°46'46.14"N. Longitude 123°32'57.40"W.

(NAD 1983 (CORS 96))