

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 658)

Set post, 4x4", 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Cedar, 40" dia., bears S.41°W., 13 lks., mkd: ¼ S BT.
Cedar, 36" dia., bears S.12°E., 41 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13512-3)

The ¼ sec. cor. of secs. 32 & 33 determined at rec. bearing & dist. from the orig. BTs:

- A Cedar, 60" dia., bears S.12°E., 41 lks. with scribe mkd. BT ¼S visible on partly healed blaze.
- A Cedar, 53" dia., bears S.41°W., 13 lks. with scribe mkd. BT ¼S visible on partly healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 32 | S 33
T 21 S R 7 W
1964

from which new BTs

- A Hemlock, 30" dia. bears N.42½°E., 156 lks. mkd: ¼ S33 BT
- A Cedar, 45" dia., bears N.89°W., 93 lks., mkd: ¼ S32 BT.

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent - 4/2018 - C.S. File 65/101-28

Found - BLM Brass cap (properly mkd)
60" Cedar S.11°E., 22.9 ft. (Rec. S.12°E., 41 lks, 27.1 ft.) rescribed ¼ S32 BT.
46" Cedar stump (7' high) N.89°W., 61.4 ft good scar
54" Cedar stump (7' high) S.41°W., 8.6 ft. good scar
New - A 56" Oak N.6°W., 63.4 scribed ¼ S32 BT.
Note - Dec. 15½°E.