TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 659)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 30" dia., bears S.66°E., 13 lks., mkd: ¼ S BT.
Fir, 20" dia., bears S.65°W., 60 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13515)

Point for ¼ sec. cor. of secs. 28 & 29, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 29|S 28
T 21 S R 7 W
1964

from which
A Fir, 12" dia., bears S.26¼°E., 13 lks., mkd: ¼ S28 BT.
A Fir, 10" dia., bears S.87°W., 19 lks., mkd: ¼ S29 BT.

Fd. & used on BLM Dependent resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, under Group #1318, surveyed May/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18317-18)

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21630-1)

The ¼ sec. cor. of secs. 28 and 29, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.
from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964
A decayed fir stump, 16" dia., bears S.26¼°E., 8.6 ft., with a healed blaze.
A fir snag, 13" dia., bears S.87°W., 12.5 ft., with a healed blaze.
and new bearing trees
A fir, 7" dia., bears S.27¼°E., 31.4 ft., mkd. ¼ S28 BT.
A fir, 20" dia., bears S.80¾°W., 24.2 ft., mkd. ¼ S29 BT.
Corner is located on W. edge fir of reproduction, edge bears N. and S.