TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 660-1)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 24" dia., bears S.30°W., 4 lks., mkd: ¼ S BT.
Fir, 24" dia., bears S.49°E., 61 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13518)

Point for ¼ sec. cor. of secs. 20 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 20|S 21
T 21 S R 7 W
1964

from which
A Fir, 26" dia., bears S.25°E., 35½ lks., mkd: ¼ S21 BT.
A Fir, 16" dia., bears S.61°W., 27½ lks., mkd: ¼ S20 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21633-4)

The ¼ sec. cor. of secs. 20 and 21, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964
A fir, 31" dia. bears S.25°E., 23.4 ft with a healed blaze
A shattered fir stump, size indeterminate, bears S.61°W., 18.2 ft., no marks visible.
and a new bearing tree
A fir, 12" dia., bears N.41¼°W., 157.0 ft., mkd. ¼ S20 BT. Tree is located on W. edge of overgrown graveled road, 20 ft. wide, bears N.20°W. and S.20°W.
Corner is located W., 1/2 ft. of fir, 3 ft. diam., with International Paper Co. property sign, on the E. edge of fir reproduction, edge bears N. and S.