

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 661)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 16, 17, 20, & 21, mkd. T 21 S S 16 on NE, R 7 W S 21 on SE, S 20 on SW, S 17 on NW face, with 4 notch(es) on E & 3 on S edges; from which

- Fir, 40" dia. bears N.47°W., 90 lks. mkd: T21S R7W S17 BT.
- Fir, 30" dia. bears S.22°W., 65 lks. mkd: T21S R7W S20 BT
- Fir, 30" dia. bears S.60°E., 78 lks. mkd: T21S R7W S21 BT.
- Fir, 36" dia, bears N.61°E., 68 lks. mkd: T21S R7W S16 BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13519)

-----  
The cor of secs 16, 17, 20, & 21 determined from the orig BTs  
A cedar, 42" dia., bears N.61°E., 68 lks., with scribe marks T21S R7W visible on opened blaze. (Rec. calls this tree a fir)

A decayed Fir stump, 20" dia., bears S.60°E., 78 lks., with no marks remaining.

A Fir, 60" dia., bears S.22°W., 65 lks., with scribe marks BT S visible on scaled bark blaze.

A Fir, 55" dia., bears N.47°W., 95 lks., with fragmentary scribe marks visible on badly scaled bark blaze. (Rec. dist. 90 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T 21 S R 7 W	
<u>S 17</u>	<u>S 16</u>
S 20	S 21
1964	

from which new BTs

- A Fir, 13" dia bears N.79¼°E. 20½ lks mkd: T21S R7W S16 BT
- A Fir, 15" dia. bears S.47¼°E. 43 lks mkd: T21S R7W S21 BT
- A Fir, 22" dia bears S.86½°W. 69½ lks mkd T21S R7W S20 BT
- A Fir, 17" dia. bears N.53°W. 29 lks. mkd: T21S R7W S17 BT

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21623-4)

-----  
The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which the remains of the orig. BTs  
continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A cedar, 44" dia., bears N.61°E., 44.9 ft. with illegible marks visible on partially healed blaze.  
A decayed fir stump, 20" dia., bears S.60°E., 50.6 ft. no marks visible, with a hemlock, 3" dia., growing out of the S. side. (Rec. 51.5 ft.)  
A fir, 54" dia. bears S.22°W., 42.9 ft. with a healed blaze. (Record, 60" dia.)  
A fir, 56" dia., bears N.47°W., 62.7 ft. no marks visible.  
and the bearing trees mkd. by Brooks and Jelley in 1964  
A fir, 17" dia. bears N.79¼°E. 13.5 ft with a healed blaze  
A fir, 23" dia. bears S.47¼°E. 28.4 ft with a healed blaze  
A fir, 34" dia., bears S.86½°W., 45.9 ft., with axe marks on bark.  
A fir, 26" dia., bears N.53°W., 19.1 ft., with axe marks on bark.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2619, Surveyed March/May 2011 - (DCSO records BLM Plat T21-7W 2012-1 & Vol. 58 Pages 22943-4)

-----  
The cor. of secs. 16, 17, 20, & 21, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of the orig. BTs

A cedar, 46" dia., bears N.61°E., 44.9 ft. with fragmentary scribe marks visible on a partially healed blaze.  
A decayed fir stump, 20" dia., bears S,60°E., 50.6 ft. with no marks visible.  
A fir, 62" dia., bears S.22°W., 42.9 ft. with a healed blaze.  
A fir, 58" dia., bears N.47°W., 62.7 ft. with a healed blaze.  
and a BTs mkd. by Brooks and Jelley  
A fir, 17" dia., bears N.79¼°E., 13.5 ft. with a healed blaze.  
A fir, 35" dia., bears S.86½°W., 46.7 ft., with a healed blaze.  
A fir, 29" dia., bears N.53°W., 19.1 ft., with a healed blaze.

(NAD 1983 (CORS 96))  
Latitude 43°44'06.64"N Longitude 123°32'45.52"W