

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 662)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
 Fir, 24" dia., bears N.35°E., 18 lks., mkd: ¼ S BT.
 Fir, 16" dia., bears S.40°W., 45 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Int. Paper Co., Long-Bell Div. - April 1970 - M 39-76

Set by proportionate measurement
Set - 5/8" steel rod rebar & scribed:
 5" Fir S.29°E., 11.6 ft.
 36" Fir N.24½°W., 23.4 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2619, Surveyed March/May 2011 - (DCSO records BLM Plat T21-7W 2012-1 & Vol. 58 Pages 22943-4)

The ¼ sec cor of secs 16 & 17, reestablished by proportionate measurement by Haines, in 1970. There is no evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with a rebar, 5/8" dia., firmly set, projecting 6" above ground, from which the BTs mkd by Haines

 A fir, 15" dia., bears S.29°E., 11.9 ft. with a healed blaze.

 A fir, 49" dia., bears N.25¼°W., 24.6 ft. with a healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

 T21S R7W
 ¼
 S 17|S 16
 2012

Place rebar, 36" long, inside and deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located 45 ft. E of an overgrown gravel road, 15 ft. wide, bears N. & S.