

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 662-3)

Set post, 5" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 8, 9, 16, & 17, mkd. T 21 S S 9 on NE, R 7 W S 16 on SE, S 17 on SW, S 8 on NW face, with 4 notch(es) on East & South edges; from which
 Fir, 24" dia., bears N.30°E., 78 lks. mkd: T21S R7W S9 BT.
 Fir, 40" dia., bears S.35°E., 8 lks. mkd: T21S R7W S16 BT.
 Fir, 24" dia., bears N.36°W., 36 lks. mkd: T21S R7W S8 BT.
 Fir, 6" dia. bears S.32°W., 95 lks. mkd: T21S R7W S17 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Aug. 7, 1958 - C.S. File 49/20-6

Found - Orig. 40", now 50" Fir S.35°E., 5.3 ft. shows good bark scribing.
 Orig. 24" now 40" N.30°E., 51.5 ft. shows good bark scribing.
 No trace of orig. SW or NW BT.
Set brass cap under 48" log which is 5' above ground. Mkd. brass cap $\frac{S\ 8\ S\ 9}{S17\ S16}$ T21S R7W COUNTY SURVEYORS OFFICE 1958
New BTs- 14" Hemlock S.74°E., 5.3 ft. mkd: S16 T21S R7W CS BT
 24" R.Fir N.58½°E., 42.0 ft., mkd: S9 T21S R7W CS BT
 16" Maple N.41°W., 31.9 ft., mkd: S8 T21S R7W CS BT
 No trees near to SW.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2619, Surveyed March/May 2011 - (DCSO records BLM Plat T21-7W 2012-1 & Vol. 58 Pages 22943-4)

The cor. of secs. 8, 9, 16, and 17, perpetuated by Bryon, in 1958, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd. from which the remains of the orig. BTs
 A Roothole bears N.30°E., 51.5 ft. downhill of which is a fallen fir snag, size indeterminate, with no marks visible.
and BTs mkd by Byron
 A fir, 33" dia., bears N.58¼°E., 41.5 ft. with no marks visible.
 A hemlock, 24" dia., bears S.79¼°E., 4.9 ft. with a healed blaze.
 A maple, 29" dia., bears N.39¼°W., 31.0 ft. with no marks visible.

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and a new BT

An alder, 5" dia., bears S.6¼°W., 43.3 ft., mkd: X BT.

Add a collar of stone around the iron post.

Corner is located 45 ft. N of a creek, 3 ft. wide, course N.60°E., and 145 ft. W of the same creek, 2 ft. wide, course East.